



**If You Ordered a Raw Brass Fixture**

All raw brass will age/darken over time. If you wish to keep your fixture “like new” you can clean it periodically with Brasso. When installing, **WE DO RECOMMEND WEARING GLOVES**. The raw brass will tarnish if it comes in contact with the oils on your skin.

**Installation Instructions**

	<p>1. Locate your Canopy(F), slip ring(G), Drop Rod(H) and mounting hardware kit. Your kit should include: A. Crossbar                      D. Hex Nut B. Allen Wrench                E. Lock Washer C. 1 1/2” Screws                H. Drop rod</p>
	<p>2. Run the fixture wires through the drop rod and thread the drop rod into the top of the fixture. Some short drop rod fixtures will come with the rod already attached. 3. Loosen the slip ring screw and slide it onto the drop rod followed by the canopy. Let the ring and canopy gently rest on the fixture during installation.</p>
	<p>4. With the ground screw pointing down, thread the wires through the center hole of the crossbar and screw it onto the drop rod. 5. Slide the lock washer than hex nut on to the drop rod and tighten.</p>
	<p>6. Attach the crossbar to the electrical box using the adjustable holes and 1 1/2” screws. 7. Attach the fixture ground wire and the electrical box ground wire (if applicable) to the ground screw 8. Attach the black and white fixture wires to their corresponding electrical box wires using wire nuts (not included). Tuck the connected wires inside the electrical box.</p>
	<p>9. Slide the canopy and slip ring up the drop rod until it is snugly against the ceiling 10. Tighten the slip ring screw using the allen wrench.</p>

