WALLHOGS

Photo-Tex EXS Application Instructions

Application

1. Select an area large enough to display your Photo-Tex wall decal print. Your print must be at room temperature prior to installing. Remove the print from shipping container and unroll. Let stand at room temperature for 60-90 minutes. If area has recently been painted, paint must be allowed to cure 30 days prior to installing your wall graphic.

2. Clean the area selected, **using water only**, to ensure no dirt or residue will adhere to the adhesive backing of your Photo-Tex EXS print. ***DO NOT USE SOAP OR ANY HOUSEHOLD CLEANING PRODUCT.*** Dry the surface thoroughly with a clean cloth and let stand for approximately 90 minutes to ensure the area is completely free from any moisture.

3. Depending upon the size of your image, the following steps are best performed by two people.

4. Once your application area is prepared simply peel the print from the white paper backing. If your image is taller than wider, begin at the top and peel toward the bottom. If wider than taller, peel from right to left.

5. PLEASE ENSURE THE AREA YOU HAVE SELECTED IS LARGE ENOUGH FOR YOUR PRINT AND THAT WHEN PROCEEDING WITH THE FOLLOWING STEPS YOU ALIGN THE PRINT DURING INSTALL SINCE THE PERMANENT ADHESIVE MAY REMOVE PAINT IF REMOVAL IS ATTEMPTED FOR REPLACEMENT.

6. Once your print has been completely peeled from the backing each of the two installers should hold one of the top corners. Place the print to the area you have selected to display it and press the top corners to the wall. BE SURE TO NOT LET THE ADHESIVE BACKING ADHERE TO ANY OTHER PART OF THE PRINT.

7. Beginning from center of image and using your hand, apply pressure and rub from center to outer edges to apply. If you encounter any air bubbles or wrinkles, simply lift the print from the closest corner and reapply.

Removal

1. If it becomes necessary for you to remove your Photo-Tex EXS print you will want to use a heat gun to heat the print while removing since the adhesive is considered permanent. Start at an out side edge of the print and slowly peel back while heating. This is no guarantee that the adhesive will remove paint or scar wall, however it should help.