

Wallhogs Decal Application & Removal Instructions

Application

1. Select an area large enough to display your wall decal print. Your print must be at room temperature prior to installing. Remove the print from shipping container and unroll. Let stand at room temperature for 60-90 minutes. If area has recently been painted, paint must be allowed to cure 30 days prior to installing your wall graphic.
2. Clean the area selected, **using water only**, to ensure no dirt or residue will adhere to the adhesive backing of your print. **DO NOT USE SOAP OR ANY HOUSEHOLD CLEANING PRODUCT.** Dry the surface thoroughly with a clean cloth and let stand for approximately 90 minutes to ensure the area is completely free from any moisture.
3. Once your application area is prepared simply peel the print from the white paper backing and apply to cleaned application surface area.
4. Beginning from center of image and using your hand, apply pressure and rub from center to outer edges to apply. If you encounter any air bubbles or wrinkles, simply lift the print from the closest corner and reapply.
5. Roll and store white paper backing in the shipping tube for future use in the event you decide to remove and store your wall decal print.

Removal

1. Simply peel the print, **SLOWLY**, from the surface and reapply to another area or place onto paper backing for storage. **DO NOT remove from an application surface unless temperature is above 60 degrees as image may tear.**

Tips & Tricks

- Air bubbles can be removed by taking a soft, dry cloth and pushing the air bubble toward the nearest edge.
- If used outside and temperature is below 60 degrees F, do not attempt to remove your decal.
- Always store you wall decal print in a temperature controlled environment.