



Waterproofing/Anti-Fracture Fabric

DS-237.0-0314

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

Waterproofing / Anti-Fracture Fabric

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 235

Toll Free: 1.800.243.4788, ext. 235

Fax: +1.203.393.1684

Internet: www.laticrete.com

3. PRODUCT DESCRIPTION

Waterproofing/Anti-Fracture Fabric is a thin, flexible non-woven fabric designed for use specifically with latex based membranes. The Waterproofing/ Anti-Fracture Fabric adds strength to load-bearing waterproofing membranes specifically for the special requirements of ceramic tile, stone and brick installations. A self-curing liquid rubber polymer and the Waterproofing/Anti-Fracture Fabric are quickly applied to form a flexible, seamless membrane that bonds to a wide variety of substrates.

Uses

See data sheet for the specific membrane being used for suitable uses

Advantages

- Required for use with 9235 Waterproofing Membrane, full fabric applications and Blue 92 Anti-Fracture Membrane
- Required for use with HYDRO BARRIER™ in coves, corner and changes of plain for waterproofing applications
- Can be used with HYDRO BAN®, Air & Water Barrier, WATERTIGHT™ Floor N' Wall Waterproofing & Crack Isolation or 9237 Waterproofing Membrane for added strength
- Interior and exterior use
- Vertical and horizontal surfaces (including ceilings)
- Provides added strength to installation areas with added stress

Suitable Substrates

See data sheet for the specific membrane being used for suitable substrates.

Packaging

300 ft² (27.8 m²) roll fabric 38" (965 mm wide)

75 ft (23 m) long roll fabric 6" (150 mm wide)

Approximate Coverage

See data sheets for the specific latex based Membrane.

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >32°F (0°C) and 110°F (43°C).

Limitations

- For installation over Glass Mat Gypsum Exterior Sheathing Panels use Air & Water Barrier only. Refer to DS661.0 & 661.5 for specific installation instructions.
- Do not use with a membrane as a primary roofing membrane over occupied space
- Do not use with a membrane over expansion joints, structural cracks or cracks with vertical differential movement
- Do not use with a waterproofing membrane over cracks >1/8" (3 mm) in width
- Do not use with a waterproofing membrane as a vapor barrier (especially in steam rooms)
- Not for use with a membrane directly over OSB, particle board, luan, Masonite®, or hardwood floors unless specifically stated as a suitable application in the membrane data sheet.
- Do not expose unprotected membranes to sun or weather for >30 days
- Do not expose membranes to negative hydrostatic pressure, excessive vapor transmission, rubber solvents or ketones
- membranes must be covered with ceramic tile, stone, brick, concrete, screeds, terrazzo or other traffic-bearing course, unless otherwise noted in specific membrane data sheet. Use protection board for temporary cover.
- Obtain approval by local building code authority before using waterproofing membrane in shower pan applications.
- Do not install a membrane directly over single layer wood floors, plywood tubs/showers/ fountains or similar constructs

Cautions

Consult specific membrane MSDS for more safety information.

- Protect from traffic or water until fully cured

4. TECHNICAL DATA

Applicable Standards

See the individual membrane data sheets for specific technical data.

Approvals

Go to www.laticrete.com or see the individual data sheets for specific product approvals.

5. INSTALLATION

Refer to data sheet of specific latex based membrane for installations instructions.

6. AVAILABILITY AND COST

Availability

LATICRETE® and LATAPOXY materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line Distributor information, visit LATICRETE at www.laticrete.com.

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM

DS 230.13: LATICRETE Product Warranty (United States and Canada)

See individual waterproofing membrane data sheets for specific warranty information.

8. MAINTENANCE

LATICRETE and LATAPOXY grouts require routine cleaning with a neutral pH soap and water. All other LATICRETE and LATAPOXY materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 235

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at www.laticrete.com. The following is a list of related documents:

DS 230.13:	LATICRETE Product Warranty (United States and Canada)
DS 105.0:	HYDRO BARRIER™
DS 236.0:	9235 Waterproofing Membrane
DS 633.0:	LATAPOXY 300 Adhesive
DS 641.0:	9237 Waterproofing Membrane
DS 661.0:	Air & Water Barrier
DS 663.0:	HYDRO BAN®
DS 660.0:	WATERTIGHT™ Floor N'Wall Waterproofing & Crack Isolation
DS 6200.1:	LATICRETE LATASIL™
DS 003.9:	WATERTIGHT Floor N'Wall Waterproofing & Crack Isolation Instructions
DS 105.5:	HYDRO BARRIER Installation Instructions
DS 663.5:	HYDRO BAN Installation Instructions
DS WPAF.5:	Fabric Reinforced Membrane Installation Instructions
TDS 152:	"Bonding Ceramic Tile, Stone or Brick Over Wood Floors"
TDS 169:	"Flood Testing Procedures"
TDS 189:	9235 Waterproofing Membrane Checklist