



### **INSTALLATION TIPS**

During installation, handle tile with care to prevent marring the surface. Leather tile is heat and moisture sensitive and not appropriate for wet areas or in areas where its surface will exceed the ambient room temperature.

Tempered Leather tile is intended for dry-stack, groutless installation. Use standard tile installation technique and for best results we recommend full coverage with a dark colored mortar. Cutting: non-toothed, diamond blade saw. No wet saw usage recommended.

# INSTALLATION PRODUCTS

Use polymer modified mortar preferably not white. We recommend the products below or equal.

Tested installation products

- · Bostik Reflex Ultra-Premium Polymer-Modified Thin Set Mortar
- · Bostik Big Tile & Stone Polymer-Modified Large & Heavy Tile Mortar
- · Bosti-Set Thin Porcelain Tile Panel Adhesive & Sound Reduction Membrane

# HOW TO FINISH AN EDGE

Installations can be finished off with matching pencil trim, metal tile edge, wood or other framing.

# **CLEAN UP**

Gentle dusting with a soft cloth. Leather cleaner and conditioner can be used at the customer's discretion.

### For additional information and project photos visit www.realstone.com

For installation instructions always refer to local building codes and consult your trained installation professional.

REALSTONE DISCLAIMS ALL LIABILITY FOR THE INSTALLATION OF THE PRODUCTS PURCHASED, AND LEAVES UP TO THE CUSTOMER AND CUSTOMER'S TRAINED INSTALLATION PROFESSIONAL THE SELECTION OF THE MATERIALS AND METHODS APPROPRIATE FOR THE USE AND INSTALLATION OF THE PRODUCT IN THE CUSTOMER'S SPECIFIC LOCATION AND CIRCUMSTANCES.