



LATASIL™ 9118 Primer

DS-6528.1-0414

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

LATASIL™ 9118 Primer

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 235

Toll Free: 1.800.243.4788, ext. 235

Fax: +1.203.393.1684

Internet: www.laticrete.com

3. PRODUCT DESCRIPTION

LATASIL 9118 Primer is a one component primer designed to increase adhesion of LATASIL to various substrates.

Uses

- Increases adhesion & bond strength for dependable long lasting installations
- For all underwater and permanent wet area applications such as pools, fountains, showers, tubs, spas, saunas and steam rooms
- Ideal for stone applications
- Ideal for harsh environment

Advantages

- Ready to use
- Fast dry time
- Durable bond is unaffected by water

Suitable Substrates

- PVC
- Stone
- Ceramic/masonry
- Metals/steel
- Porcelain

Packaging

- 8 oz. (240 ml) bottle; 5 bottles per carton.

Approximate Coverage

- Each bottle will cover approximately 350 linear feet (106 linear meters).

Shelf Life

When stored in original, unopened containers at or below 90°F (32°C), shelf life is 6 months from date of manufacture. Container should be kept tightly sealed when not in use.

Limitations

- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE® Waterproofing Membrane (see Section 9 FILING SYSTEMS).
- Flammable—cannot be shipped air freight.

Cautions

Consult MSDS for more safety information.

- Avoid direct contact with eyes. If contact with eyes occurs, immediately flush with water and seek medical attention.
- Avoid prolonged exposure to skin. In case of skin contact, wash affected area as soon as possible.
- Keep away from heat, sparks and open flames.
- Use with adequate ventilation, avoid prolonged breathing of vapors.
- Flammable—store in safe location.
- Test a small area when applying to stone for compatibility.
- Keep out of reach of children.

4. INSTALLATION

Preparation

- Thoroughly clean all surfaces of dust, dirt tar, oils, and other debris. Remove rust and scale from metal surfaces by abrasive cleaning or wire brushing. Masonry surfaces should also be wire brushed and blown with compressed air to remove dust.
- Thoroughly clean and degrease all surfaces with an industrial solvent such as naphtha, mineral spirits, xylene, toluene or MEK on a clean oil-free rag.

Application

- Sealant must be installed in the manner indicated for intended performance.

- Consult the following details at www.laticrete.com for specific sealant installation applications:
 - Shower Receptor–Waterproofing-Cement Backer Unit Walls ES B415
 - Shower Receptor–Waterproofing Above Mortar Bed ES B421
 - Bathtub/Shower Wall Waterproofing ES B412
 - Waterproofing Membrane-Typical Pipe Penetration ES WP300
 - Drain Detail-Exploded View ES WP302
 - Waterproofing and Secondary Waterproofing Membrane-Drain Detail ES WP303
 - Swimming Pool-Tank ES P601
 - Swimming Pool-Pool Deck/Trench Drain ES P601c
 - For underwater applications and steam rooms, polyethylene foam backer rod is recommended. Use polyethylene tape on joints too shallow to accommodate foam rod. Polyethylene backer rod is a “closed” cell which is water repellent.
- Apply LATASIL™ 9118 Primer to clean, dry surfaces by brushing, dipping, or spraying.
- Apply a thin layer evenly to the substrate-do not apply too thick as bond will break.
- Take care not to contaminate the veneer surface.
- Allow the primer to dry until all the solvent evaporates and is dry to the touch (generally 30–60 minutes at 70°F/21°C). Drying time depends on temperature, humidity conditions and the porosity of the substrate.
- Apply sealant as directed (see DS 6200.1).

5. AVAILABILITY AND COST

Availability

LATICRETE® and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788
Telephone: +1.203.393.0010

For on-line Distributor information, visit LATICRETE at www.laticrete.com.

Cost

Contact a LATICRETE Distributor in your area.

6. WARRANTY

See 9. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty (United States and Canada)

A component of:

DS 230.05APD: LATICRETE 5 Year Tile & Stone System Warranty (United States and Canada)

DS 230.15APD: LATICRETE 15 Year Tile & Stone System Warranty for Steel or Wood Framed Exterior Facades (United States and Canada)

DS 230.15SPD: LATICRETE 15 Year System Warranty – MVIS For Steel or Wood Framed Exterior Facades (United States and Canada)

DS 025.0APD: LATICRETE 25 Year Tile & Stone System Warranty (United States and Canada)

DS 025.0SPD: LATICRETE 25 Year System Warranty- MVIS (United States and Canada)

DS 230.99: LATICRETE Lifetime Tile & Stone System Warranty (United States and Canada)

7. MAINTENANCE

LATICRETE and LATAPOXY grouts require routine cleaning with a neutral pH soap and water. All other LATICRETE and LATAPOXY materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

8. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 235
Telephone: +1.203.393.0010, ext. 235
Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com.

9. FILING SYSTEM

Additional product information is available on our website at www.laticrete.com. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty (United States and Canada)
DS 230.05APD: LATICRETE 5 Year Tile & Stone System Warranty (United States and Canada)
DS 230.15APD: LATICRETE 15 Year Tile & Stone System Warranty for Steel or Wood Framed Exterior Facades (United States and Canada)
DS 230.15SPD: LATICRETE 15 Year System Warranty – MVIS For Steel or Wood Framed Exterior Facades (United States and Canada)
DS 025.0APD: LATICRETE 25 Year Tile & Stone System Warranty (United States and Canada)
DS 025.0SPD: LATICRETE 25 Year System Warranty-MVIS (United States and Canada)
DS 230.99: LATICRETE Lifetime Tile & Stone System Warranty (United States and Canada)
DS 236.0: 9235 Waterproofing Membrane
DS 6200.1: LATASIL™

LATICRETE International, Inc.
One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

©2014 LATICRETE International, Inc.
All trademarks shown are the intellectual properties of their respective owners.