



25.10.2.018

Carpets Inter®

Carpets Inter® apply strict quality control at all stages of production, in compliance with ISO 9001. However, the carpet manufacturing process is a complex series of operations and variations in the specifications could occur. This will not have any detrimental effect on the performance of the product. We reserve the right to amend this specification without prior notice.

Breaking Ground | Flatlands Machine Tufted Carpet Tile

Specifications

Collection		Breaking Ground Flatlands
Construction		Multi Level Texture Tufted
Yarn Content		100% Solution Dyed Nylon
Machine Gauge		1/10 inch
Pile Height		3-4 mm 0.118-0.157 inch
Pile Weight		441 gm/sm 13.0 oz/sy
Total Weight		2880 gm/sm 84.94 oz/sy
Primary Backing		Non Woven Polyester Spunbonded
Secondary Backing		EcoSoft™ Reinforced Recycled Backing
Tile Size		50 x 50 cm


Performance Test and Treatment

Critical Radiance Flux		ISO9239-1:2010 8.3kW/m ²
Indoor Air Quality		CRI Green Label Plus
Electrostatic Propensity		AATCC 134 Permanent Anti-Stat ≤ 3.0 KV
Overall Classification		BS EN 1307 Heavy
Castor Chair Rating		BS EN 985 ≥ 2.4 Continuous use
Dimensional Stability		BS EN 986 ≤ 015%
Colourfastness to Light		ISO 105 B02 Minimum 6
Treatments		Stain and Soil Resistant, Anti Microbial (Optional)

Installation Method

50 x 50 cm

25 x 100 cm



Checkerboard



Herringbone

Certification and Standards



EcoSoft™
 Environmentally Friendly Cushion Backing,
 Recycled and Recyclable Materials.



FL 06 Akanda



FL 15 Matobo



FL 09 Ruma



FL 16 Katavi



FL 10 Sapo



FL 18 Karoo