

e info@floorspace.co.nz
 p + 64 9 271 5946
 o800 space1 (77 22 31)



09.08.2019

Carpets Inter®

Carpets Inter® apply strict quality control at all stages of production, in compliance with ISO 9001. However, the carpet manufacturing process is a complex series of operations and variations in the specifications could occur. This will not have any detrimental effect on the performance of the product. We reserve the right to amend this specification without prior notice.


Specifications

Collection	Upstream Ebb & Flow
Construction	Multi Level Texture Tufted
Yarn Content	100% Solution Dyed Nylon
Machine Gauge	1/12 inch
Pile Height	3-5 mm
Total Weight	2820 gm/sm
Backing	EcoSoft™ Recycled Cushion Backing
Tile Size	25 x 100 cm

Performance Test and Treatment

Overall Classification	BS EN 1307 Class 33 - Heavy Commercial
Castor Chair Rating	BS EN 985 ≥ 2.4
Dimensional Stability	BS EN 986 < 0.15%
Electrostatic Propensity	AATCC 134 < 3 KV
Colourfastness to Light	ISO 105 B02 Minimum L6
Flammability	ISO 9239-1:2010 CRF 8.3
Sound Absorption	BS EN ISO 354 NRC 0.30 or higher (Superior Noise Reduction)
Treatments	Stain and Soil Protection

Installation Method



Random Vertical Brick



Herringbone

Certification and Standards



EcoSoft™
 Environmentally Friendly Cushion Backing,
 Recycled and Recyclable Materials.

Upstream | Ebb & Flow Machine Tufted Carpet Tile


Ebb



EB01 Spring



EB02 Creek



EB03 River



EB04 Estuary



EB05 Ocean


Flow




FW01 Ripple



FW02 Backwash



FW03 Wake



FW04 Tide



FW05 Drift