POLICY STATEMENT CLINOFISH "The performance of our products must exceed all others on the World Market" KGM Pratty



PURE AND POLISHED POND WATER.

Clinofish® is a specific type of Zeolite mineral exclusively mined in South Africa. It is a direct substitute for fish pond filter media that scavenges toxic Ammonia from pond water. It is a true 21st century filter medium with both ion exchange and superior mechanical filtration properties.

Unlike ordinary filter media. Clinofish acts as a filter on the atomic scale by absorbing toxic Ammonia (which can kill fish stocks even at extremely small concentrations!) from pond water. This is due to a powerful negative charge that exists within the Clinofish structure that attracts positively charged cation contaminants such as

Ammonia and holds them within the Clinofish structure. Also, unlike ordinary filter media such as gravel or sand, the surfaces of Clinofish particles are not smooth and therefore have large surface areas. Clinofish is therefore an extremely effective biological media for maximum colonization of useful, nitrifying bacteria.

WHY USE CLINOFISH?

- Controls Ammonia in agua culture and fish hatchery water treatment.
- Reduces fish mortality.
- Improves water quality and water clarity in your pond.
- Maximises fish growth.
- Improves water quality for high density fish transportation.
- Ideal substrate for biological filters.
- Improves the quality of water discharged from recirculating systems.
- Removes heavy metals and ionic inorganic toxins.
- It can be used over again after simple regeneration.




CLINOFISH[®] IS A DIRECT SUBSTITUTE FOR FILTER SAND





You can regenerate Clinofish. Remove the Clinofish from the ilter and place in a bath or trough. Add a solution of brine (10% salt solution or 1kg rock salt per 10lt water) over Clinofish so that it is fully submerged in the salt solution. Leave in order to remove absorbed Ammonia from the Clinofish overnight. Rinse Clinofish with fresh water a few times to remove excess salt.

STEP 1 Fill half the filter tank with water.



STEP 3

In intervals of approximately 15 seconds, alternate several times between the backwash and the rinse cycle on your filter valve. This removes any fines generated during transport.


BACKWASH

STEP 2 Slowly add Clinofish® to half the tank volume & close the lid.



STEP 4

- a backwash water clarity check by either observing the clear window on the filter valve or examining the clarity of the water exiting your discharge pipe.



Pratley (Pty) Ltd. PO Box 3055 • KENMARE 1745 • Gauteng South Africa Tel: +27 11 955-2190/8 • Fax: +27 11 955-3918 • email: sales@pratley.co.za www.clinofish.com

3