

TECHNOLOGY



COLOR HIGH-VOLUME MULTIFUNCTION PRINTER

Up to 65 ppm print/copy output to keep pace with rising demands
Standard dual scanning handles up to 240 originals per minute
High capacity 300-sheet document feeder
Large 10.1" color display with quick tablet-like touchscreen interface
Scan-to-email and FTP, scan-to-me, scan-to-home convenience
Built-in Emperon® print system, universal printer drivers
Simitri® HD polymerized toner for high-resolution imaging
Standard 250 GB HDD for on-board document storage
Web browser with 4 GB of memory
ISO 15408 and IEEE 2600.1 security standards

Power-saving design with quick recovery from sleep mode
6,650-Sheet maximum capacity, tab printing support, carbon-copy printing
Advanced authentication, secure print release, remote firmware updates
Multiple bypass tray and detachable paper feed trays improve paper handling
Finishing options for 80-page booklet-making, up to 100-sheet stapling
Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more
Downloadable apps to help you work faster and smarter
Multiple i-Options to suit the needs of your workflow
EPEAT Gold-certified, low power consumption to cut costs
Mobile printing support (AirPrint, Google Cloud Print Classic, NFC)

bizhub C659

COLOR HIGH-VOLUME MULTIFUNCTION PRINTER

Superior color, spectacular speed and simple touch-and-swipe operation make the bizhub C659 an ideal document solution for high-volume applications. Output speeds of 65 ppm plus duplex scanning at up to 240 opm keep work flowing — and you'll have powerful, scalable options to increase your productivity and help control your costs.

CVC	TERA	O	/EDI	/IEW
313	LEIVI	U	/ERI	IEVV

SISILINI OVERVIEW	
System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T / 100-BASE-TX / 1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB v2, LPD, IPP, SNMP, HTTP
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3	1,500 sheets / 5.5" x 8.5", 4" x 6" / 52-256 gsm
Tray 4	1,000 sheets / 5.5" x 8.5", 4" x 6" / 52-256 gsm
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
LU-205 (optional)	40 Value 10 California 10 Cali
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-303 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" /
	custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold,
	post-insertion, booklet
Output capacity	Max. with finisher: 3,300 sheets
	Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 300,000 pages / month ¹
Toner lifetime	Black: 48,900 pages / CMY: 33,200 pages
Imaging unit lifetime	Black: 300,000 pages / 1,200,000 pages (Drum/Developer)
	CMY: 200,000 pages
Power consumption	120 V / 60 Hz, less than 2.1 kW (system)
System dimensions	25.5" x 31.5" x 45.5" (W x D x H)
System weight	Approx. 487 lb.
,	and P Production (CC)

COPIER SPECIFICATIONS

Copying process	Electrostatic laser copy, tandem, indirect	
Toner system	Simitri® HD Polymerized Toner	
Print speed (8.5" x 11")	B&W / Color: up to 65 / 65 ppm (Portrait)	
Print speed (11" x 17")	B&W / Color: up to 33 / 33 ppm (Portrait)	
Autoduplex speed	B&W / Color: up to 65 / 65 ppm (Portrait)	
(8.5" x 11")		
1st copy out time	B&W: 3.7 sec. / Color: 4.9 sec.	
Warm-up time	B&W: approx. 22 sec. ² / Color: 35 sec. ²	
Copy resolution	600 x 600 dpi	
Gradations	256 gradations	
Multi-copy	1-9,999	
Original format	Up to 11" x 17"	
Magnification	25-400% in 0.1% steps, auto zooming	
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1	

PRINTER SPECIFICATIONS (STANDARD)

	JIIJ (JIANDAKD)		
Print resolution	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi		
PDL	PCL6 (XL 3.0), PCL5e/c, PostScript 3 (ver. 3016), XPS		
Operating systems	Windows (x32 / x64): 7 / 8 / 10		
	Windows Server (x32 / x64): 2008 / 2008 R23 / 20123 / 20163		
	Macintosh OS X 10.8 or later		
	Linux / Unix / Citrix		
Printer fonts	80 PCL Latin, 137 PostScript 3		
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and		
	OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy		
	Set" job programming, overlay, watermark, copy protection,		
	carbon copy print		

PRINTER SPECIFICATIONS (OPTIONAL)

Print controller Embedded Fiery IC-418 (VI-510 required)		
Memory/HDD	4 GB / 250 GB	
PDL	PostScript 3 (ver. 3019) PCL 6 / 5c	
Operating systems	Windows (x32 / x64): 7 / 8 / 10	
	Macintosh OS X 10.7 or later	

SCANNER SPECIFICATIONS

SCANNER SPECIFICATIONS		
B&W / Color: up to 240 ipm		
Max.: 600 x 600 dpi		
Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan- to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scar		
JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/ XLSX (optional)		
2,100 (shared with fax), LDAP support		
Annotation (text/time/date) for PDF, up to 400 job programs, real-time scan preview		

FAX SPECIFICATIONS

Fax	Super G3 (optional)	
Transmission Analog, Internet fax, Color i-Fax, IP-Fax		
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/FTP/SMB, up to 400 job programs	

USER BOX SPECIFICATIONS

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and
	fax), copy box-to-box



PARTNERSHIP

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

INFORMATION MANAGEMENT	IT SERVICES	TECHNOLOGY
Enterprise Content Management (ECM)	Application Services	Office Multifunction Business Solutions
Document Management	Cloud Services	Commercial and Production Printers
Automated Workflow Solutions	IT Security	3D Printers
Business Process Automation	Managed IT Services	Wide Format Printers
Security and Compliance	IT Consulting & Projects	Laptops, Desktops and
Mobility	Business Consulting Services	Computer Hardware
eDiscovery Services	5000 00 000 000 000 000 000 000 000 000	Servers and Networking Equipment
,		Managed Print Services (MPS)
		Managed Enterprise Services





For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2017 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com







SYSTEM FEATURES Security	ISO 15408 FAL3 ⁴
Security	IFFE 2600 14
	122220011
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	FIPS 140-2
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt
	Print user data encryption
26	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + Email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

Log Management Utility

Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

Warm-up time may vary depending on the operating environment and usage.

Supports x64 only.

Certification pending.

COM	DON	EMITC	AND	ODT	ONC
CUIVI	PUN	ENIS	HIND	UPI	CPIUI

COMPONENTS AND OPT	
AU-102 Biometric	Finger vein scanner
authentication	9
AU-205H Universal	Various ID card technologies
ID card reader	
AU-211	Requires WT-506 Working Table
CAC/PIV solution*	
EK-610 USB I/F kit	USB keyboard connection
EK-611 USB I/F kit	USB keyboard connection, Bluetooth
FK-516 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
	(requires MK-742)
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output
FS-536SD	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output
FS-537SD	100-sheet stapling, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
HD-524 Hard disk	Backup HDD
IC-418 Fiery image	Embedded image controller for graphics-intensive applications
controller	
JS-602 Job separator	Separation for fax output, etc.
for FS-537	
Keyboard	External keyboard (requires KH-102)
KH-102	To place USB keyboard
Keyboard holder	w 5
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3	PDF/A, PDF encryption, digital signature
LK-104 v3	Provides voice guidance functions
LK-105 v4	Searchable PDF
LK-106	Supports native barcode printing

	(CONTINUED)

LK-107	Supports native Unicode printing		
LK-108	Supports native OCR A and B font printing		
LK-110 v2	Generates various file formats incl. DOCX, XLSX and		
	combines LK-102 (encrypted PDF) + LK-105 (searchable PDF)		
	OCR functionality)		
LK-111	ThinPrint® Client data compression for		
	reduced network impact		
LU-205	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm		
Large capacity unit			
LU-303	3,000 sheets / 8.5" x 11" / 52-256 gsm		
Large capacity unit			
MK-715 Mount kit	Banner paper guide		
MK-735 Mount kit	Installation kit for ID card reader		
MK-742 Mount kit	Installation kit for FK-515 fax board		
OT-508 Output tray	Output tray used instead of finisher		
PI-507 Post inserter	Cover insertion, post finishing		
for FS-537			
PK-520 Punch kit	2/3-hole punching, autoswitching		
for FS-536			
PK-523 Punch kit	2/3-hole punching, autoswitching		
for FS-537			
RU-515 Relay unit	Required for FS-537/FS-537SD and FS-536/FS-536SD		
SC-508 Security kit	Copy Guard function (2x required)		
SK-602 Staple kit	Added stapling functionality kit		
SP-501 Stamp unit	Added fax stamp capability kit		
UK-212 Wireless LAN	Wireless LAN to network connector		
UK-501 Multi-feed	Detects multi-feeding in the document feeder		
detection kit			
VI-510 Interface kit	Fiery controller interface card		
for IC-418			
WT-506 Working table	Authentication device placement		
WT-513 Upright	Required to mount the control panel in an upright position,		
working table	can also be used to hold authentication devices		
ZU-609 Z-fold unit	Z-fold for 11" x 17" prints		
for FS-537			

for FS-537
* May not be available at time of launch.

