

## **bizhub C200 full color printer copier scanner fax**

MOVE UP TO BIZHUB – IN COLOR AND B&W. To keep ahead of competition, small-to-mid-size offices must move faster – and moving up to bizhub is an ideal solution. 20 ppm output in both color and B&W make the bizhub C200 a superb replacement for overstressed printer/copiers. With paper sizes up to 12" x 18", weights up to 140 lb. index stock and 3,350-sheet maximum capacity, you can handle any document needs. Scanning at up to 40 originals per minute brings information into your system faster. Sleek design, small footprint and 360° styling looks great anywhere in your office. You'll also have high-impact Simitri® HD color, Energy Star certification to protect the environment, ultra-quiet operation – plus options like auto-reversing document feeder, auto duplexing and fax/Internet fax/IP fax to handle high-volume communications traffic.











BUILT-IN EMPERON® PRINT SYSTEM, PCL/PS FUNCTIONALITY

IMAGING WITH SIMITRI® HD COLOR POLYMERIZED TONER

FLEXIBLE SCANNING: UP TO 40 OPM IN B&W, 20 OPM IN COLOR

 MULTI-METHOD SEND FUNCTION, SCAN-TO-EMAIL

250-SHEET STANDARD, 3,350-SHEET MAXIMUM PAPER CAPACITY

SUPPORTS UP TO 140 LB. INDEX IN ALL TRAYS, UP TO 12" X 18" PAPER

REVERSING AUTO DOCUMENT FEEDER & DUPLEXING OPTIONS

SECURE PRINT OPTION TO PROTECT DOCUMENTS IN THE DIGITAL ERA

SUPER G3 FAX OPTION, INTERNET FAX AND IP ADDRESS FAX

"ASSISTANT TOOL FOR C200" FOR ADDRESS REGISTRATION AND SSL

ULTRA-QUIET OPERATION, ENERGY STAR EFFICIENCY



## bizhub C200

FULL COLOR \_PRINTER \_COPIER\_SCANNER \_FAX\_

CONNECT COMMUNICATE CONTRO

## General Specifications:

TYPE: PRINT/COPY PROCESS: TONER TYPE

MONTHLY DUTY CYCLE: PRINT/COPY SPEED:

PRINT RESOLUTION: SCAN SPEED: SCAN RESOLUTION:

SCAN FILE FORMATS: MEMORY:

HARD DISK DRIVE

GRADATION ORIGINAL SIZE COPY SIZE

WARM UP TIME FIRST COPY TIME

COPY QUANTITY: MAGNIFICATION:

COLOR MODES: COPY EXPOSURE MODES FAXING (OPTIONAL):

DATA COMPRESSION: FAX TRANSMISSION SPEED: FΔX MFMORY-

FAX EXPOSURE MODES: STANDARD PAPER CAPACITY: OPTIONAL PAPER CAPACITY:

MAXIMUM PAPER CAPACITY:

DOCUMENT FEEDER (OPTIONAL): POWER REQUIREMENTS:

POWER CONSUMPTION: DIMENSIONS (W x D x H) WEIGHT

AVAILABLE PRINT/COPY FUNCTIONS:

AVAILABLE SCAN FUNCTIONS: AVAILABLE FAX FUNCTIONS:

HDD:

PAGE DESCRIPTION LANGUAGE: FONTS:

PRINT DRIVERS INTERFACE: PROTOCOLS USER TOOLS

Full Color Printer/Copier/Scanner with Stationary Platen

aser Tandem Process

Simitri® HD Color Polymerized Toner

Full Color: 20 ppm (letter, portrait), B&W: 20 ppm (letter, portrait)

600 dpi equivalent x 600 dpi

Full Color: 20 opm (@ 300 dpi, letter), B&W: 40 opm (@ 300 dpi, letter)

200 dpi, 300 dpi, 400 dpi, 600 dpi

TIFF, PDF, JPEG

576 MB (64 MB File Memory + 512 MB Working Memory) standard, 1088 MB maximum

256 color shades per pixel

Up to 11" x 17" (A3) (scanning/copying), Up to 11" x 17" full bleed on 12" x 18" paper (printing)

Tray 1 (multi purpose cassette): 4" x 6" to 12" x 18" (A6 to A3 wide) Full Color: Less than 40 seconds, B&W: Less than 37 seconds

Full Color: Less than 13.5 seconds. B&W: Less than 10 seconds

Zoom range: 25% - 400%, 0.1% increments, Preset reduction: 79%, 77%, 65%, 50%, Preset enlargement: 121%, 129%, 155%, 200%

Auto Color, Full Color, Black & White, 2-Color, Single Color

Text (legible text), Text/Photo (clear text and halftones), Photo (optimized for gradations), Map (fine edges and legible text), Light Text

Super G3 compatibility; JBIG data compression; 33.6 Kbps modem speed

MH MR MMR JRIG

Less than 3 seconds/page (V.34, 33.6 Kbps, JBIG, standard resolution)

576 MB (shared copier memory)

Text, Text/Photo, Photo, Light Text, Map

250-sheet multi purpose cassette (16 lb. bond to 140 lb. index) (60 g/m² to 256 g/m²)

500-sheet universal cassette (16 lb. bond to 140 lb. index) (60 g/m² to 256 g/m²), 500-sheet x 1 universal cassette (16 lb. bond to 140 lb. index) (60 g/m² to 256 g/m²) 500-sheet x 2 universal cassette (16 lb. bond to 140 lb. index) (60 g/m² to 256 g/m²), 2500-sheet universal cassette (16 lb. bond to 140 lb. index) (60 g/m² to 256 g/m²),

Multi Bypass Tray 100-sheet (16 lb. bond to 140 lb. index) (60 g/m² to 256 g/m²

3,350 sheets (total, with options)

DF-612 Auto Document Feeder, Speed: Simplex: Color: 20 opm (@ 300 dpi) B&W: 40 opm (@ 300 dpi); Paper Capacity: 70 sheets, Paper Size: 5.5" x 8.5" to 11" x 17" (A3 to A5)

Paper Weight: Single-sided: 10 lb. bond to 34 lb. bond (38 g/m² to 128 g/m²), Double-sided or mixed: 13.25 lb. bond to 34 lb. bond (50 g/m² to 128 g/m²)

20V, 60Hz Less than 1250 W

24.5" x 27.75" x 25.5" (622 x 705 x 648 mm)

150 lb. (68 Kg)

AD-505 Automatic Duplex Unit, OC-508 Original Cover, DF-612 Reversing Automatic Document Feeder, MB-502 Multi Bypass Tray, PC-104 Paper Feed Cabinet, PC-105 Paper Feed Cabinet

PC-204 Paper Feed Cabinet, PC-405 Paper Feed Cabinet, DK-504 Copy Desk, JS-505 Job Separator, FK-507 Fax Kit, ML-504 Fax Multi-Line Kit, SP-503 Fax Stamp Unit, MS-501 Spare TX Marker Stamp 2

EM-310 Expanded Memory Unit

Account Track, APS/AMS, Auto Duplex, Auto Tray Switching, Color Modes & Functions (Auto Color/Full Color, Black & White Mode, Single Color Mode, 2-Color Mode), Color Adjustments (Brightness, Contrast Saturation, Sharpness, Red, Green, Blue, Color Balance, Copy Density), Copy Modes (Simplex/Duplex, 2-in-1, 4-in-1), Creative Functions (Neg./Pos. Reverse), Criss-Cross Sorting, Energy Save Mode, Finishing (Group, Sort, Shift Sort), Glossy Mode, Image Density Adjustment (Background Removal), Image Rotation, Interrupt, Job List, Margin Setting (Print Only), Mix Originals, Multi-Job

Overlay (Print Only), Paper Size Selection (APS/Manual), Paper Type Selection (Normal, Thick 1, Thick 2, Thick 3), Print Modes (Simplex/Duplex, 2-in-1, 4-in-1, 6-in-1, 9-in-1, 16-in-1, 2x2, 3x3, 4x4), Program Registration, Secure Printing, Utility (Meter Count, Default Setting, One-Touch Setting, Check Consumables Life, Admin. Mode), Watermarks (Print Only), Zoom Selection (AMS, User Programmable

Zoom Ratio, Manual) Scan-to-Email

Autodialing (300 one-touches), Broadcast Transmission, Bulletin Setting, Duplex Transmission, Exposure Mode (Text, Text/Photo, Photo, Light Text, Map), TX Forwarding, Image Rotation Transmission/Reception, Internet Fax, IP Address Fax (B&W Only), Memory Reception, Memory RX, Memory Transmission, Overseas Transmission, PC-Fax, Polling Transmission, Profity Transmission, PC-Fax, Polling Transmission, PC-Fax, PC Program Dialing (30 programs), Quick Scan Transmission, Redial, Remote Copy/Output, Rotation Transmission/Reception, Timer Transmission, 2-in-1 Transmission

## Emperon Print System (standard):

PROCESSOR: 667 MHz Power PC 440EP RAM: 576 MB (shared copier memory)

PCL5e/c, PCL XL version 3.0 Emulation, PostScript 3 (version 3015)


PCL: 80 fonts, Postscript 3 Emulation: 137 fonts

Server: Windows 2000, Windows Server 2003, Windows Server 2003, Windows Server 2003 x64, Client: Windows 2000/XP/Vista, Windows XP/Vista x64 Edition, Mac OS 9.2, Mac OS X version 10.2-10.4/Mac Intel OS X 10.4

Ethernet (10BASE-T/100BASE-TX), USB 2.0

TCP/IP (LPD/LPR RAW) Assistant Tool for C200







www.kmbs.konicaminolta.us www.konicaminolta.us/solutions









© 2008 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Konica Minolta is a trademark and The essentials of imaging is a registered trademark of KONICA MINOLTA HOLDINGS, INC. bizhub and Emperon are registered trademarks of KONICA MINOLTA BUSINESS TECHNOLOGIES, INC. Simitri is a registered trademark of KONICA MINOLTA BUSINESS SOLUTIONS. All product names