


PRODUCT SPECIFICATIONS



Main Unit

Type

Color Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store

Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

Standard: 10.1" TFT LCD WSVGA Color Touch-panel

Optional: 10.4" TFT LCD WSVGA Color Upright-panel

Memory

4.0 GB RAM

Hard Disk Drive

Standard: 250 GB

Maximum: 1 TB

Mirroring Hard Disk Drive

Optional (250 GB, 1 TB)

Method: Raid1

Print Resolution

2400 dpi x 2400 dpi

Interface Connection

Network

Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)

Optional: NFC, Bluetooth

Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 3,550 Sheets

Maximum: 9,300 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: Two 1,100-sheet Paper Drawers, Two 550-sheet Paper Cassettes, 250-sheet Stack Bypass

Optional: 3,500-sheet Paper Deck (Paper Deck Unit-E1), 3,500-sheet Paper Deck (Pod Deck Lite-C1), 6,000-sheet Paper Deck (Multi-Drawer Paper Deck-C1)

Maximum: 9,300 Sheets (With Multi-Drawer Paper Deck-C1)

Paper Output Capacity (LTR, 20 lb. Bond)

250 Sheets (with Copy Tray-R2)

3,500 Sheets (with External Finisher-V2)

4,250 Sheets (with External Finisher-X1)



Finishing Capabilities

Standard: Collate, Group
With Finishers: Collate, Group, Offset, Staple, Booklet, Hole Punch, Staple-Free Staple, Staple On Demand, Document Insertion, Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold, Trimming

Supported Media Types

Paper Thin, Plain, Recycled, Color, Heavy,
Drawers Pre-punched, Letterhead, Bond,
(1/2): Transparency
Paper Thin, Plain, Recycled, Color, Heavy,
Cassettes Pre-punched, Letterhead, Bond,
(3/4): Transparency, Tab, Envelope
Stack Bypass: Thin, Plain, Recycled, Color, Heavy,
Pre-punched, Labels, Letterhead,
Bond, Coated, Transparency, Tab,
Tracing, Envelope, Textured

Supported Media Sizes

Paper Drawers
(1/2): Letter
Paper 13" x 19", 12" x 18", 11" x 17", Legal, Letter,
Cassettes Letter-R, Executive, Statement-R,
(3/4): Envelope [No.10 (COM10), Monarch,
DL, ISO-C5], Custom Size (5-1/2" x 7-1/8"
to 13" x 19-1/4"), Envelope Custom Size
(3-7/8" x 5-7/8" to 13" x 19-1/4")
Stack Bypass: 13" x 19", 12" x 18", 11" x 17", Legal, Letter,
Letter-R, Executive, Statement-R,
Envelope [No.10 (COM10), Monarch, DL,
ISO-C5], Custom Size (4" x 5-7/8" to
13" x 19-1/4"), Envelope Custom Size
(3-1/2" x 3-7/8" to 13" x 19-1/4"), Free Size
(4" x 7-1/8" to 13" x 19-1/4")

Supported Media Weights

Paper Drawers: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)
Paper
Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Warm-up Time

From Power On: 30 Seconds or Less
From Deep Sleep Mode: 30 Seconds or Less
Quick Startup Mode: 4 Seconds¹

Dimensions (W x D x H)

27-1/8" x 37-1/8" x 48" (689 mm x 941 mm x 1,220 mm)

Installation Space (W x D)

Basic [With Booklet Finisher-V2 (Stack Bypass and Cassette Drawers Open)]:
75-3/8" x 60" (1,913 mm x 1,524 mm)
Fully Configured [With Multi-Drawer Paper Deck-C1+Document Insertion Unit-N1+Multi Function Professional Puncher-A1+Document Insertion Unit-N1+Booklet Finisher-X1 (Cassette Drawers Open)]:
150-3/8" x 60" (3,818 mm x 1,524 mm)

Weight

Approx. 595.2 lb. (270 kg)²

Print Specifications

Print Speed (BW/Color)

iR ADV Up to 80/70 ppm (Letter); Up to 60/52
C7580i: ppm (Letter-R); Up to 47/41 ppm (Legal);
Up to 40/35 ppm (11" x 17")
iR ADV Up to 70/65 ppm (Letter); Up to 52/48
C7570i: ppm (Letter-R); Up to 41/38 ppm (Legal);
Up to 35/32 ppm (11" x 17")
iR ADV Up to 65/60 ppm (Letter); Up to 48/45
C7565i: ppm (Letter-R); Up to 38/35 ppm (Legal);
Up to 32/30 ppm (11" x 17")

Data Processing Resolution

Up to 1200 dpi x 1200 dpi

Standard Page Description Languages

UFR II, PCL[®]6, Adobe[®] PS[®]3

Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access (Opt.)³

Supported File Types for Direct Print

PDF, TIFF, JPEG, EPS,⁴ XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),⁵ Barcode Fonts⁶

PS fonts: 136 Roman

Operating System⁷

UFR II: Windows Vista[®]/Server 2008/Windows[®] 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.6.8 or later)
PCL: Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10
PS: Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.6.8 or later)
PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows Vista/Windows 7/Windows 8/Windows 8.1/Windows 10

Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Forced Hold Printing, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Reduction, Poster Printing

Copy Specifications

Copy Speed (BW/Color)

iR ADV Up to 80/70 ppm (Letter); Up to 60/52
C7580i: ppm (Letter-R); Up to 47/41 ppm (Legal);
Up to 40/35 ppm (11" x 17")
iR ADV Up to 70/65 ppm (Letter); Up to 52/48
C7570i: ppm (Letter-R); Up to 41/38 ppm (Legal);
Up to 35/32 ppm (11" x 17")
iR ADV Up to 65/60 ppm (Letter); Up to 48/45
C7565i: ppm (Letter-R); Up to 38/35 ppm (Legal);
Up to 32/30 ppm (11" x 17")

First-Copy-Out Time (Letter)

iR ADV As fast as 4.4 seconds (BW)/
C7580i: 5.4 seconds (Color)
iR ADV As fast as 4.8 seconds (BW)/
C7570i: 5.9 seconds (Color)
iR ADV As fast as 4.8 seconds (BW)/
C7565i: 5.9 seconds (Color)

Copy Resolution

Reading: Up to 600 dpi x 600 dpi
Printing: 2400 dpi x 2400 dpi

Multiple Copies

Up to 9,999 copies

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Detect Feeder Multi Sheet Feed, Free Size Original, Color Balance, Adjust One-Touch Color, Area Designation

Scan Specifications

Type

Color Platen and Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity

300 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 80 lb. Cover
(50 to 220 g/m²)

CL Original: 17 lb. Bond to 80 lb. Cover
(64 to 220 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)]

Pull Scan

Color Network ScanGear2 for both Twain and WIA
Supported OS: Windows Vista/7/8/8.1/10
Windows Server 2003/Server 2003 R2/
Server 2008/Server 2008 R2/Server
2012/Server 2012 R2

Scan Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100dpi

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (Letter)

Single-sided Scanning (BW):
120 ipm (300 dpi)/120 ipm (600 dpi)
Single-sided Scanning (Color):
120 ipm (300 dpi)/70 ipm (600 dpi)
Double-sided Scanning (BW):
240 ipm (300 dpi)/150 ipm (600 dpi)
Double-sided Scanning (Color):
220 ipm (300 dpi)/90 ipm (600 dpi)

Send Specifications

Destination

E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

Color Mode

Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and-White), Full color, Grayscale, and Black-and-White

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100dpi

Communication Protocol

File: FTP, SMB, WebDAV
E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

File Format

Standard: TIFF, JPEG, PDF(Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b), XPS (Compact, Searchable), Office Open XML (PowerPoint®, Word)

Optional: PDF (Trace & Smooth, Encrypted), PDF/XPS (Digital Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

Fax Specifications

Maximum Number of Connection Lines

4

Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

Sending/Recording Size

Statement-R to 11" x 17"

Fax Memory

Up to 30,000 pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 dials

Sequential Broadcast

Max. 256 addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

Store Specifications

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV

Supported

Client PC: Windows (Windows Vista/7/8/8.1/10)

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

Advanced Box Available Disk Space

Approx. 16 GB (Standard HDD)

Approx. 480 GB (1 TB HDD)

Advanced Box Features:

Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in

Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated)

Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Standard: IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

Document

Standard: Secure Print, Forced Hold Printing, Adobe LiveCycle® Rights Management ES2.5 Integration

Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan Locking

Environmental Specifications

Operating Environment

Temperature: 50 to 86°F

Humidity: 20 to 80% RH (no condensation)

Power Requirements

C7580i: 208 V AC, 60 Hz, 12 A

C7570i/7565i: 120-127 V AC, 60 Hz, 16 A

Plug (Main Unit)

C7580i: NEMA 6-15P

C7570i/7565i: NEMA 5-20P

Power Consumption

Maximum

C7580i: Approx. 2.5 kWh

C7570i/7565i: Approx. 2.0 kWh

Standby: Approx. 119.2 W

Sleep Mode: Approx. 0.9 W⁸

Typical Electricity Consumption (TEC) Rating:

C7580i: 5.5 kWh

C7570i: 4.6 kWh

C7565i: 4.5 kWh

Standards

ENERGY STAR® Certified

Rated EPEAT® Gold⁹

RoHS Compliant

Consumables

Toner

GPR-56 Toner

Toner Yield (Estimated @ 5% Coverage)

Black: 82,000 Images

Color (C,M,Y): 66,500 Images

Fiery Print Controller Specifications (Optional)

ColorPASS-GX500 (External)

System

Fiery FS200 Pro

Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

Standard Page Description Languages

Adobe PS 3, PCL5 (Driverless)

Memory

4 GB

Hard Disk Drive

1 TB

Processor

Intel Core i5-4570S 2.9 GHz up to 3.6 GHz w/Turbo

Fonts

PS: 138 Adobe PS Fonts

PCL: 113 PCL Fonts

Supported Operating Systems

Windows Vista (32 and 64 bit)/Windows 7 (32 and 64 bit)/Windows 8 (32 and 64 bit)/Windows 8.1 (32 and 64 bit)/Windows 10 (32 and 64 bit)/Windows Server 2008 (32 and 64 bit)/Windows Server 2008 R2 (64 bit only)/Windows Server 2012 (64 bit only)/Windows Server 2012 R2 (64 bit only)/MAC OS (10.7, 10.8, 10.9, 10.10, 10.11)

Interface

2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x 6 (Front x 2, Rear x 4), USB2.0 x 2 (Front x 2)

Network Protocols

TCP/IP (LPR/Port 9100/SNMP/IPP/HTTP/HTTPS/FTP/SMB)/DNS

Direct Print

PDF1.7(APPE3), EPS, TIFF6, JDF1.4/JMF

VDP

FreeForm2.1, PDF/VT-2, PPML3, VPS

Fiery Print Controller Standard Features

Fiery Hot Folders/Virtual Printers/Unity Display (Monitor Required)/Fiery JDF/Fiery Command Workstation 5/Paper Catalog/Fiery Spot-On/Fiery Remote Scan

Fiery Print Controller Options

Fiery Impose, Fiery Compose, Fiery Impose and Compose, Graphic Arts Package Premium Web Activate/Removable HDD Kit-B1/Integration Interface and Stand (19" Display, Keyboard and Mouse)

Dimensions (W x D x H)

8-1/2" x 19" x 19-1/8" (215 mm x 483 mm x 485 mm)

imagePASS-N1 (Embedded)

System

Fiery FS200

Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

Standard Page Description Languages

PCL6, Adobe PS 3

Memory

2 GB

Hard Disk Drive

500 GB

Processor

Intel Celeron G1820 2.7 GHz

Fonts

PS: 138 Adobe PS Fonts

PCL: 113 PCL Fonts

Supported Operating Systems

Windows Vista (32 and 64 bit)/Windows 8 (32 and 64 bit)/Windows 8.1 (32 and 64 bit)/Windows 7 (32 and 64 bit)/Windows Server 2008 (32 and 64 bit)/Windows Server 2008 R2 (64 bit only)/Windows Server 2012 (64 bit only)/Windows Server 2012 R2 (64 bit only)/MAC OS (10.7 or higher)

Interface

2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB x 3.0 x 2 (Rear x 2), USB x 2.0 x 4 (Rear x 4)

Network Protocols

TCP/IP (LPR/Port 9100/SNMP/IPP/HTTP/HTTPS/SMB/FTP)/DNS

Fiery Print Controller Features

Fiery Command Workstation 5, Paper Catalog, Fiery Spot On, Fiery Remote Scan, Hot Folders License

Fiery Print Controller Options

Fiery Impose, Fiery Compose, Fiery Impose and Compose, Productivity Package Web Activate (Includes Fiery JDF)

Dimensions (W x D x H)

11-1/4" x 3-5/8" x 11-5/8" (285 mm x 93 mm x 295 mm)

Paper Supply Options

PAPER DECK UNIT-E1

Paper Capacity: 3,500 Sheets [20 lb. Bond (80 g/m²)]

Paper Type: Thin, Plain, Recycled, Color, Heavy, Pre-punched, Letterhead, Bond

Paper Size: Letter

Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)

Power Source: From the Main Unit

Dimensions (W x D x H): 14-1/4" x 24-7/8" x 22-1/2" (363 mm x 630 mm x 572 mm)

Weight: 75 lb. (34 kg)

POD DECK LITE-C1

Paper Capacity: 3,500 Sheets [20 lb. Bond (80 g/m²)]

Paper Type: Thin, Plain, Recycled, Color, Heavy, Pre-punched, Label, Letterhead, Bond, Coated, Transparency, Tab, Tracing, Envelope,¹⁰ Textured

Paper Size: 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Custom Size (5-1/2" x 5-7/8" to 13" x 19-1/4")

Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Power Requirements: 120-127 V AC, 60 Hz, 2.2 A

Dimensions (W x D x H): 25-7/8" x 27" x 22-1/2" (656 mm x 686 mm x 570 mm)

Weight: Approx. 149.9 lb. (68.0 kg)

MULTI-DRAWER PAPER DECK-C1

Paper Capacity: 6,000 Sheets [20 lb. Bond (80 g/m²)]

Paper Type: Thin, Plain, Recycled, Color, Heavy, Pre-punched, Label, Letterhead, Bond, Coated, Transparency, Tab, Textured

Paper Size: 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (5-1/2" x 7-1/8" to 13" x 19-1/4")

Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Power Requirements: 120-127 V AC, 60 Hz, 3.1 A

Dimensions (W x D x H): 37-3/8" x 31-3/8" x 41" (950 mm x 797 mm x 1,040 mm)

Weight: Approx. 341.7 lb. (155.0 kg)

Output Options

STAPLE FINISHER-V2

Number of Trays: 3

Top Tray Capacity: Letter/Executive/Statement-R (250 Sheets), 11" x 17"/Legal/Letter-R (125 Sheets)

Mid Tray Capacity: Letter/Executive/Statement-R (250 Sheets), 11" x 17"/Legal/Letter-R (125 Sheets)

Lower Tray Capacity: Letter/Executive/Statement-R (3,000 Sheets), 13" x 19"/12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)

Paper Weight

Top Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)

Mid Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)

Lower Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Staple Position: Corner, Double

Staple Capacity

Corner Staple and Double Staple

Letter/Executive: 65 Sheets [24 lb. Bond (90 g/m²)]

11" x 17"/Legal/Letter-R: 30 Sheets [24 lb. Bond (90 g/m²)]

Staple-Free Staple:

11" x 17"/Letter: 5 Sheets [14 to 17 lb. Bond ((52 to 64 g/m²)]
4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m²)]
3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m²)]

Staple On Demand: 65 Sheets [24 lb. Bond (90 g/m²)]

Power Requirements: 100-240 V AC, 50/60 Hz, 2.8 A

Dimensions (W x D x H): 25-7/8" x 24-1/2" x 47-1/8" (656 mm x 623 mm x 1,195 mm)¹⁰

Weight: Approx. 77.2 lb (35 kg)

STAPLE FINISHER-X1

Number of Trays: 3

Top Tray Capacity: Letter/Executive/Statement-R (1,500 Sheets), 13" x 19"/12" x 18"/11" x 17"/Legal/Letter-R (750 Sheets)

Mid Tray Capacity: Letter/Executive/Statement-R (250 Sheets), 11" x 17"/Legal/Letter-R (125 Sheets)

Lower Tray Capacity: Letter (2,500 Sheets)

Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Staple Position: Corner, Double

Staple Capacity

Letter/Executive: 100 Sheets [20 lb. Bond (80 g/m²)]

11" x 17"/Legal/Letter-R: 50 Sheets [20 lb. Bond (80 g/m²)]

Power Requirements: 100-240 V AC, 50/60 Hz, 2.8 A

Dimensions (W x D x H): 30-3/4" x 30-1/8" x 41" (782 mm x 765 mm x 1,040 mm)¹¹

Weight: Approx. 141.1 lb (64 kg)

BOOKLET FINISHER-V2

Number of Trays: 3

Top Tray Capacity: Letter/Executive/Statement-R (250 Sheets), 11" x 17"/Legal/Letter-R (125 Sheets)

Mid Tray Capacity: Letter/Executive/Statement-R (250 Sheets), 11" x 17"/Legal/Letter-R (125 Sheets)

Lower Tray Capacity: Letter/Executive/Statement-R (3,000 Sheets), 13" x 19"/12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)

Paper Weight

Top Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)

Mid Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)

Lower Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Staple Position: Corner, Double

Staple Capacity

Corner Staple and Double Staple

Letter/Executive: 65 Sheets [24 lb. Bond (90 g/m²)]

11" x 17"/Legal/Letter-R: 30 Sheets [24 lb. Bond (90 g/m²)]

Staple-Free Staple

11" x 17"/Letter: 5 Sheets [14 to 17 lb. Bond ((52 to 64 g/m²)]
4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m²)]
3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m²)]

Staple On Demand: 65 Sheets [24 lb. Bond (90 g/m²)]

Booklet-Stitch Paper Size: 12" x 18", 11" x 17", Legal, Letter-R, Custom Size (7-3/4" x 10-5/8" to 12" x 18")

Booklet-Stitch Staple Capacity: 20 Sheets x 10 Sets [22 lb. Bond (81 g/m²)] [including one cover sheet up to 140 lb. Index (256 g/m²)]

Power Source: From the Main Unit

Dimensions (W x D x H): 25-7/8" x 24-1/2" x 47-1/8" (637 mm x 623 mm x 1,195 mm)¹¹

Weight: Approx. 127.9 lb (58 kg)

BOOKLET FINISHER-X1

Number of

Trays: 3

Top Tray Capacity: Letter/Executive/Statement-R (1,500 Sheets), 13" x 19"/12" x 18"/11" x 17"/Legal/Letter-R (750 Sheets)

Mid Tray Capacity: Letter/Executive/Statement-R (250 Sheets), 11" x 17"/Legal/Letter-R (125 Sheets)

Lower Tray Capacity: Letter (2,500 Sheets)

Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Staple Position: Corner, Double

Staple Capacity

Letter/Executive: 100 Sheets [20 lb. Bond (80 g/m²)]

11" x 17"/Legal/Letter-R: 50 Sheets [20 lb. Bond (80 g/m²)]

Booklet-Stitch Paper Size: 13" x 19", 12" x 18", 11" x 17", Legal, Letter-R, Custom Size (8-1/4" x 11" to 13" x 19-1/4")

Booklet-Stitch Staple Capacity: 20 Sheets x 5 Sets [16 to 22 lb. Bond (60 to 81.4 g/m²)] [including one cover sheet up to 110 lb. Cover (300 g/m²)]

Power Requirements: 100-240 V AC, 50/60 Hz, 2.8 A

Dimensions (W x D x H): 35-1/4" x 30-1/8" x 41" (896 mm x 765 mm x 1,040 mm)¹²

Weight: Approx. 242.5 lb (110 kg)

2/3-HOLE PUNCHER UNIT-A1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)

Acceptable

Punch Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Acceptable Punch Paper Size

Two holes: 11" x 17", Legal, Letter, Letter-R, Executive

Three holes: 11" x 17", Letter, Executive

Power Source: From the Main Unit

PUNCHER UNIT-BF1

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)

Acceptable

Punch Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)

Acceptable Punch Paper Size

Two holes: 11" x 17", Legal, Letter, Letter-R, Executive

Three holes: 11" x 17", Letter, Executive

Power Source: From the Finisher

MULTI FUNCTION PROFESSIONAL PUNCHER-A1

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)

Acceptable Punch Paper Weight

Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Punch: 20 lb. Bond to 110 lb. Cover (75 to 300 g/m²)

Acceptable

Punch Paper

Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R

Supported Punch Dies

(Optional): Loose Leaf (3-hole, 5-hole), Plastic Comb

19-hole, Velo Bind 11-hole, Twin Loop

21-hole/32-hole, Color Coil 44-hole

Power

Requirements: 115 V AC, 60 Hz, 3.8 A

Dimensions

(W x D x H): 17-1/2" x 31-3/8" x 41" (445 mm x 795 mm x 1,040 mm)

Weight: Approx. 224.9 lb (102 kg)

INNER BOOKLET TRIMMER-A1

(Requires the BOOKLET FINISHER-X1)

Trim Capacity: 40 Sheets

Waste Tray

Capacity: 1,500 Sheets

Acceptable 13" x 19", 12-5/8" x 17-1/16", 12" x 18", 11" x 17",

Paper Size: Legal, Letter-R, Custom Size (8-1/4" x 11" to 13" x 19-1/4")

Acceptable 16 lb. Bond to 110 lb. Cover

Paper Weight: (60 to 300 g/m²)

Power Source: From Finisher

DOCUMENT INSERTION UNIT-Q1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)

Number of

Trays: 1

Tray Capacity: 100 Sheets [20 lb. Bond (80 g/m²)]

Acceptable Thin, Plain, Recycled, Color, Heavy,

Paper Type: Letterhead, Bond, Coated, Tab, Textured

Acceptable 13" x 19", 12" x 18", 11" x 17", Legal, Letter,

Paper Size: Letter-R, Executive

Acceptable 16 lb. Bond to 140 lb. Index

Paper Weight: (60 to 256 g/m²)

Power

Requirements: 100-240 V AC, 50/60 Hz, 1 A

Plug: NEMA 5-15P

Dimensions 26-1/8" x 26-3/4" x 48-7/8"

(W x D x H): (662 mm x 679 mm x 1,242 mm)¹²

Weight: Approx. 88.2 lb (40 kg)

DOCUMENT INSERTION/FOLDING UNIT-K1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)

Number of

Trays: 1

Tray Capacity: 100 Sheets [20 lb. Bond (80 g/m²)]

Acceptable Thin, Plain, Recycled, Color, Heavy,

Paper Type: Letterhead, Bond, Coated, Tab, Textured

Acceptable 13" x 19", 12" x 18", 11" x 17", Legal, Letter,

Paper Size: Letter-R, Executive

Acceptable 16 lb. Bond to 140 lb. Index

Paper Weight: (60 to 256 g/m²)

Support Fold

Types: C-Fold, Z-Fold

Acceptable

Fold Paper

Type: Thin, Plain, Color, Recycled

Acceptable Fold Paper Size

C-Fold Size: Letter-R

Z-Fold Size: 11" x 17", Legal, Letter-R

Acceptable

Fold Paper 16 lb. Bond to 28 lb. Bond

Weight: (60 to 105 g/m²)

Power

Requirements: 100-240 V AC, 50/60 Hz, 1 A

Plug: NEMA 5-15P

Dimensions 26-1/8" x 26-3/4" x 48-7/8"

(W x D x H): (662 mm x 679 mm x 1,242 mm)¹³

Weight: Approx. 167.6 lb (76 kg)

DOCUMENT INSERTION UNIT-N1

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)

Number of

Trays: 2

Tray Capacity: Upper/Lower Tray: 200/200 Sheets

[20 lb. Bond (80 g/m²)]

Acceptable Thin, Plain, Recycled, Color, Heavy,

Paper Type: Pre-punched, Letterhead, Bond,

Coated, Tab, Tracing, Textured

Acceptable 13" x 19", 12" x 18", 11" x 17", Legal, Letter-R,

Paper Size: Executive, Custom Size (7-1/8" x 7-1/8" to

13" x 19-1/4")

Acceptable 14 lb. Bond to 110 lb. Cover

Paper Weight: (52 to 300 g/m²)

Power

Requirements: 100-240 V AC, 50/60 Hz, 1 A

Plug: NEMA 5-15P

Dimensions 29-3/8" x 31-1/4" x 55-3/8"

(W x D x H): (746 mm x 793 mm x 1,407 mm)¹³

Weight: Approx. 134.5 lb (61 kg)

PAPER FOLDING UNIT-J1

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)

Supported C-Fold, Z-Fold, Accordion Z-Fold,

Fold Type: Double Parallel Fold, Half-Fold

Acceptable

Paper Type: Thin, Plain, Recycled, Color, Bond

Acceptable Paper Size

Z-Fold: 11" x 17", Legal, Letter-R

C-Fold/

Accordion/

Z-Fold/

Half-Fold: Letter-R

Double

Parallel Fold: Letter-R, Legal

Acceptable Paper Weight

C-Fold/

Accordion/

Z-Fold/

Half-Fold: 14 lb. Bond to 28 lb. Bond (52 to 105 g/m²)

Double

Parallel Fold: 14 lb. Bond to 24 lb. Bond (52 to 90 g/m²)

Power Source: From the Finisher

Dimensions 13-1/4" x 31-1/4" x 46-7/8"

(W x D x H): (336 mm x 793 mm x 1,190 mm)

Weight: Approx. 156.5 lb. (71 kg)

Additional Hardware Options

Card Readers

MiCARD PLUS PROXIMITY CARD READER

COPY CARD READER-F1

COPY CARD READER ATTACHMENT-A4

Others

COPY TRAY-R2

UTILITY TRAY-B1

PRINTER COVER-H1

TAB FEEDING ATTACHMENT KIT-F1

USB KEYBOARD

Security Options

Document Security

DOCUMENT SCAN LOCK KIT-B1

SECURE WATERMARK-B1

ENCRYPTED SECURE PRINT SOFTWARE-D1

iR-ADV SECURITY KIT-Q1 FOR IEEE 2600 COMMON

CRITERIA CERTIFICATION¹⁴

Data Security

HDD MIRRORING KIT-J1

2.5"/250 GB HDD-N1

2.5"/1 TB HDD-P1

REMOVABLE HDD KIT-AL1

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1

Barcode Printing

BARCODE PRINTING KIT-D1

EFI-Fiery Based Controller

imagePASS-N1

ColorPASS-GX500

REMOVABLE HARD DISK DRIVE KIT-B1

FIERY IMPOSE

FIERY COMPOSE

FIERY IMPOSE AND COMPOSE

System Accessories

COPY CONTROL INTERFACE KIT-A1

CONNECTION KIT-A1 FOR BLUETOOTH LE

NFC KIT-C1

NFC KIT-A1 (For Upright Control Panel)

MEAP WEB CONNECTION KIT-G3

Fax Accessories

SUPER G3 FAX BOARD-AS2

SUPER G3 2ND LINE FAX BOARD-AS2

SUPER G3 3RD/4TH LINE FAX BOARD-AS2

REMOTE FAX KIT-A1

IP FAX EXPANSION KIT-B1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1

VOICE GUIDANCE KIT-G1

VOICE OPERATION KIT-D1

BRaille LABEL KIT-F1

Consumables

STAMP INK CARTRIDGE-C1

STAPLE-N1 (for Staple Finisher-X1 and

Booklet Finisher-X1)¹⁵

STAPLE-P1 (for Booklet Finisher-X1)¹⁶

STAPLE CARTRIDGE-X1 (for Staple Finisher-V2 and

Booklet Finisher-V2)¹⁵

STAPLE CARTRIDGE-Y1 (for Booklet Finisher-V2)¹⁶

Footnotes

¹ Time from device power-on to when copy jobs can be programmed.

² Includes main unit, ADF, and consumables.

³ PDF print from Web sites is supported.

⁴ EPS can be printed directly only from the Remote User Interface.

⁵ Requires the optional PCL International Font Set-A1.

⁶ Requires the optional Barcode Printer Kit-D1.

⁷ Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

⁸ 0.9 W Sleep mode is not available in all circumstances due to certain settings.

⁹ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.

¹⁰ Requires Envelope Feeder Attachment-G1

¹¹ When the extension tray and rotary tray are extended.

¹² When the extension tray is extended.

¹³ With the insertion feeding tray.

¹⁴ Will launch at a later date.

¹⁵ Used for corner/double stapling only. 3 cartridges per case. 5,000 staples per cartridge.

¹⁶ Used for booklet finishing only. 2 cartridges per case. 2,000 staples per cartridge.

 USA.CANON.COM



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Google Cloud Print™ is either a registered trademark or trademark of Google Inc. AirPrint and the AirPrint logo are trademarks of Apple Inc. Adobe® and PostScript® 3™ are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft® and PowerPoint® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. PCL® is a registered trademark of Hewlett-Packard Company. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2017 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

