

TOP SECRET COATINGS®

Industrial Maintenance Product Details

	Number of Components	Dry Time	Pot life	Gloss Level	Clear or Color	Horizontal Sq. Ft. Per Gallon	Vertical Sq. Ft. Per Gallon	VOCs	LEED Credits	Prop 65 Chemicals	Solvents	Antimicrobial	Odor	Flammable	Primer Needed	Slip Resistant Certified
TS-105	2	6-8hrs	90mins	>85° Gloss	Both	250	325	<30 g/l	Yes	No	No	Yes	No	No	No	Yes
TS-300	2	6-8hrs	90mins	25° Matte 55° Satin	Both	250	325	<50 g/l	Yes	No	No	Yes	No	No	No	Yes

Additives

- GripLok - to increase slip co-efficient of friction; reduces gloss to a matte / satin appearance depending on the quantity added.
- GripLok Gloss - to increase slip co-efficient of friction; larger particle uses less additive thus maintaining a glossy appearance.
- Accelerator - to shorten the dry time.
- Adhesion Plus - to increase adhesion properties to hard to adhere to surfaces such as ceramic, porcelian and other tile and grout.



Absolute Coatings Group, 1999 Elizabeth Street, North Brunswick, NJ 08902 - 866-892-3447 www.topsecretcoatings.com