

BOAT TRAILER SECURITY WINCH TS SERIES



- Winch delivered complete with strap and hook.
- Colour code indicates strap pulling capacity.
- Galvanized steel and plastic carter.

WINCH TS SERIES: AN EASY TO USE SAFETY WINCH



Simplicity

Push the strap guide in lower position and pull off the strap... Hitch the boat up.
After the tension of the strap* ... the boat is automatically secured.



Constant security

The winch holds the boat... you can unhand the handle..



Comfort of use

2 speeds to reduce the effort.
During pulling operation the winch holds the boat even without action on handle.
Up winding without load 10 times faster.

ITEMS



Winches supplied with strap and hook		TS700		TS800		TS900		TS1200		TS1600		TS2200		TS3000	
Item No		PF70700		PF70800		PF70900		PF701200		PF701600		PF702200		PF703000	
Hauling capacity (20% incline) (kg)		700		800		900		1 200		1 600		2200		3 000	
Gear ratio	Speed 1	1/3,5		1/4,85		1/4,85		1/4,85		1/4,85		1/4,85		1/10	
	Speed 2	-		-		-		1/9,71		1/9,71		1/9,71		1/21,77	
Strap	Length (m)	6,5		8		8		8		8		8		13	
	Colour	Black		Black		Yellow		Yellow		Green		Green		Green	
Max force on handle in hauling operation	Boat weight	560 kg	700 kg	590 kg	780 kg	675 kg	900 kg	900 kg	1200 kg	1200 kg	1600 kg	1600 kg	2200 kg	2400 kg	3000 kg
	Force (kg)	5	7	5	7	5	7	5	7	5	7	7	11	2	7
Handle length (mm)		200		250		290		250		290		290		290	
Winch weight (kg)		4,7		5,7		5,7		6,1		6,1		6,5		21	

MAINTENANCE AND ACCESSORIES

** Strap maintenance is achieved through replacement of the complete drum sub-assembly, delivered with strap and hook. Available at your local authorised distributor

	TS700	TS800	TS900	TS1200	TS1600	TS2200	TS3000
A	Ø11	Ø11	Ø11	Ø11	Ø11	Ø11	Ø13
B	28,5	28,5	28,5	28,5	28,5	28,5	60,25
C	70	70	70	70	70	70	128
D	22	22	22	22	22	22	10,5
E	24,5	24,5	24,5	24,5	24,5	24,5	24,75
F	28	28	28	28	28	28	25
G	130	130	130	130	130	130	210
H	46	36	36	36	36	36	-
I	53	53	53	53	53	53	85
J	200	250	290	250	290	290	290
K	186	186	186	186	186	186	252
L	430	390	430	390	430	430	518,8
M	183	208	208	208	208	208	220,5
N	119	119	119	119	119	119	177,5
O	273	273	273	273	273	273	335,4
P	17	-	-	-	-	-	-
Q	13,5	-	-	-	-	-	-
R	26,5	-	-	-	-	-	-
S	48	-	-	-	-	-	-
T	22,5	-	-	-	-	-	-



Type	Drum complete with strap, hook and strap guide**
TS700	PF56405
TS800	PF56406
TS900	PF56407
TS1200	PF56408
TS1600	PF56409
TS2200	PF56412
TS3000	PF56427 (strap and hook)



Handle length	Item No
200 mm	PF75083
250 mm	PF56410
290 mm	PF56411



Adapter plate :	Item No
For TS (Except TS3000)	PF56413

DIMENSIONS AND FIXINGS (MM)

