

WEBI PULLEY TYPE ETT-74 - GALVANISED CAST IRON PULLEY (ETTER) Quick Ref: 155.2



- **WEBI galvanised cast iron single pulley / sheave ETT-74**
- **Complete with bearing and fixing bolt**
- **Material finish - galvanised cast iron**
- **Capacities from 200 kg to 1,000 kg**
- **To suit 3 mm - 12 mm wire rope (see specification PDF for full details)**
- **For use with manual and powered winches**
- **SWISS MANUFACTURED**

- With bearing and fixing bolt
- Material - galvanized cast iron

Product code			ETT-74-50 155.2.1	ETT-74-60 155.2.2	ETT-74-70 155.2.3	ETT-74-80 155.2.4	ETT-74-100 155.2.5	ETT-74-120 155.2.6	ETT-74-150 155.2.7	ETT-74-180 155.2.8	ETT-74-210 155.2.9	ETT-74-240 155.2.10	ETT-74-300 155.2.11
Diameter of pulley	D	MM	50	60	70	80	100	120	150	180	210	240	300
Load capacity		KG	100	100	200	200	300	400	500	500	800	800	1000
Max fleet angle	FLEET ANGLE	MM	40	40	40	40	40	40	40	40	40	30	30
Rope diameter			2.5	3	3	4	4	5	6.5	8	9	10	12
Width	N	MM	19	19	26	26	30	30	34	34	38	38	38
Fixing bolt		MM	6x35	6x35	8x45	8x45	10x55	12x60	14x65	14x65	16x70	16x70	16x70
	d	MM	37	46	56	65	83	100	130	160	185	206	265
Bore	B	MM	6.2	6.2	8.2	8.2	10.2	12.2	14.2	14.2	16.5	16.5	16.5
Number bearings			1	1	2	2	2	2	2	2	2	2	2
Weight per item		KG	0.19	0.27	0.37	0.41	0.6	0.9	1.6	2	3.4	4	6.5

