

Pulley (PTM)with Bracket 55mm ϕ - Rope ϕ 2-4mm - Sheave Polyamide - Bracket Stainless Steel (304) or Zinc- 125kg SWL Quick Ref:152.14



PTM - Zinc

- A 125 kg SWL Rope Pulley Sheave made from Polyamide (PA 6)
- Complete with Steel with Zinc Coated (S235JR/ surface galvanised FeZn 12C) Bracket, for use in aggressive environments.
- Suitable for wire rope 2-4mm.
- Self weight 0.25kg

PTM - Stainless

- A 125 kg SWL Rope Pulley Sheave made from Polyamide (PA 6)
- Complete with Stainless Steel (A304) Bracket, for use in aggressive environments.
- Pulley Diameter 55mm
- Suitable for wire rope 2-4mm.
- Self weight 0.25kg

PULLEY TYPE PTM - FOR WIRE ROPE

Simple low cost pressed bracket with polyamid pulley. steel or stainless steel options.



Product code	Max capacity (kg)	Rope dia ϕ (mm)	Weight (kg)	Rope pulley material	Bracket material
PTM-125G 152.14.7	125	2-4	0.25	Polyamid	Steel, zinc coated
PTM-125SS 152.14.8	125	2-4	0.25	Polyamid	Stainless steel

