



Base mounting (KE)



Wall mounting (WE)



Lifting capacity 300 kg or 500 kg for wall mounting (WE), base or wall mounting (KE)

- Compact, modern wall or base mounted winches
- Corrosion resistant stainless steel with gears protected by plastic casing
- Large rope capacity
- Self locking internal brake with proven security concept
- Lightweight and compact shape, folding crank, fully enclosed gears and brake
- Quiet in operation
- Available in 2 versions – wall mounting (WE) or base mounting (KE) with mounting bracket

Product code KE (base or wall mounting)		HA-KE300	HA-KE500
Product code WE (wall mounting)		HA-WE300	HA-WE500
Lifting capacity 1st layer	(kg)	300	500
Lifting capacity last layer	(kg)	185	300
Rope diameter	(mm)	4	5
Rope capacity 1st layer	(m)	3.4	2.6
Rope capacity total	(m)	29	22
Number of layers		6	6
Ratio		3.1:1	4.5:1
Lift per crank turn	(mm)	64	46
Required effort (kg)	(kg)	16	20
Duty class to DIN 15020		1Em	1Em
Weight (kg)	(kg)	5	5

## DIMENSIONS (mm)

Capacity (kg)	300	500
A	337	337
B	170	170
C	135	135
D	105	105
E1	200	200
F	83	83
F1	65	65
G	160	160
H	250	250
J	130	130
K	140	140
L	60	60
MØ	11	11
NØ	13	13

## FEATURES OF THIS WINCH AT A GLANCE

Capacity	300 or 500kg
Mounting	Wall (WE) or base (KE)
Gearing	Spur
Quiet	No
Crank	Non removable
Self Sustaining	Yes

