HAND WINCH TYPE HA-WV, HA-KV



Lifting capacity 300 kg or 500 kg

- Compact, modern, braked winch for wall mounting (WV) or base or wall mounting (KV)
- Innovative winch with large rope capacity
- Corrosion resistant zinc plated with fully enclosed gears and brake encased in plastic cover
- Self locking internal brake with proven security concept
- Lightweight and compact
- Folding Crank
- Quiet in operation
- Available in 2 versions wall mounting (WV) or base mounting with mounting frame (KV)
- Stainless Steel version available

Product code WV (wall mounting)		HA-WV300	HA-WV500
Product code KV (base orwall mounting)		HA-KV300	HA-KV500
Lifting capacity 1st layer	(kg)	300	500
Lifting capacity last layer	(kg)	185	300
Rope diameter	(mm)	4	5
Rope capacity 1st layer	(m)	3.4	2.6
Rope capacity total	(m)	29	22
Number of layers		6	6
Ratio		3.1:1	4.5:1
Lift per crank turn	(mm)	64	46
Required effort	(kg)	16	20
Duty class to DIN 15020		1Em	1Em
Weight	(kg)	5	5

DIMENSIONS (mm)

Product Code	HA-WV300 / HA-KV300	HA-WV500 / HA-KV500
A	337	337
В	170	170
С	135	135
D	105	105
E1	200	200
F	83	83
F1	65	65
G	160	160
Н	250	250
J	130	130
К	140	140
L	60	60
MØ	11	11
NØ	13	13



FEATURES OF THIS WINCH AT A GLANCE				
Q	Capacity	300 or 500kg		
O	Mounting	Wall or base		
\Phi	Gearing	Spur		
O	Crank	Fixed		
Q	Self Sustaining	Yes		

