

Elizabeth

PL92T-120



TECHNICAL FEATURES

LELIT58 commercial group compatible with LELIT58 barista tools

3 ways solenoid valve to dry up the coffee puck

LCC with high-resolution OLED graphic display

Graphic indicator for lack of water in the tank and "Reserve mode"

Possibility to activate the automatic purge, the preinfusion, the stand-by and the washing cycle

Possibility to disable the steam boiler

Programmable brewing time for coffee doses

Temperature of coffee, water and steam indicated in Celsius or Fahrenheit degrees

Back-lit manometer for coffee pressure

Brushed stainless steel appliance body with drip tray and wire grate

Wide cup warmer

Back-lit stainless steel buttons

Multidirectional anti-burn steam wand and fixed hot water wand

Mug friendly

The dual boiler and the LELIT58 commercial group are Elizabeth's special features and ensure a continuous steam delivery and the extraction of a considerable quantity of water, without influencing coffee performance. The accurate choice of materials and its details make it a wonderful piece of design even when the machine is turned off.

Brass coffee boiler: 300 ml

AISI316L stainless steel steam/hot water boiler: 600 ml

Water tank: 2.5 l

Dimensions LxDxH: 32x38x38 cm

Weight: 15.3 kg

DELIVERED WITH

LELIT58 2-ways filterholder with design handle and Coffee Slide spout

LELIT58 1 dose filter (7-9 g)

LELIT58 2 doses filter (14-18 g), IMS

LELIT58 blind filter, IMS

Tamper

Spoon for coffee powder

35 l water softener filter

Cup rack

First cleaning kit

PL92T-120 120 V 60 Hz | Plug Type B