



8165 E Kaiser Blvd. Anaheim, CA 92808  
www.lightlaboratory.com

Report No: L051802301



**Report No:** L051802301

**Issue Date:** 5/22/2018

**Report Prepared For:** Horticulture Lighting Group  
752 North State St, #208, Westerville, OH 43082

**Model Number:** HLG 550 V2

**Test:** Photosynthetically active radiation (PAR) & Electrical measurement

**Standards Used:** Appropriate part or all test guidelines were used for test performed:  
*IESNA LM79: 2008* Approved Methods for Electrical and Photometric Measurements of Solid-State Lighting Products  
*ANSI NEMA ANSLG C78.377: 2008* Specification of the Chromaticity of Solid State Lighting Products  
*ANSI C82.77:2002:* Harmonic Emission Limits-Related Quality Requirements for Lighting Equipment

**Description of Sample:** Client submitted the sample. Received in working and undamaged condition. No modifications were necessary.

**Testing Condition:** Fixture is tested with no special conditions.

**Sample Arrival Date:** 5/17/18

**Date of Tests:** 5/21/18 - 5/22/18

**Seasoning of Sample:** No seasoning was performed in accordance with IESNA LM-79.

**Equipment List**

Equipment Used	Model No	Stock No	Calibration Due Date
Chroma Programmable AC Source	61604	PS-AC02	--
Yokogawa Digital Power Meter	WT210	MT-EL06-S4	1/9/19
BK PRECISION	1747	PS-DC04	1/10/19
Fluke Digital Thermometer	52K/J	MT-TP05	1/10/19
LLI 2M Sphere	2MR97	CD-SN03-S2	--
LLI Spectroradiometer	SPR-3000	MT-SC01-S2	Before Use

\*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

**Test Summary**

<b>Manufacturer:</b>	Horticulture Lighting Group	
<b>Model Number:</b>	HLG 550 V2	
<b>Driver Model Number:</b>	MEAN WELL HL-480H-C2100A	
<b>Total PPF (μmol/s)</b>	1178.05	* Measured range: 380nm - 780nm
<b>Total Radiant Flux(W):</b>	243.13	* Measured range: 380nm - 780nm
<b>Total Lumens:</b>	80833.17	* Measured range: 380nm - 780nm
<b>Efficacy (lm/W):</b>	170.93	
<b>Input Voltage (VAC/60Hz):</b>	220.00	
<b>Input Current (Amp):</b>	2.19	
<b>Input Power (W):</b>	472.90	
<b>Input Power Factor:</b>	0.98	
<b>Current ATHD @ 220V(%):</b>	6%	
<b>Current ATHD @ 277V(%):</b>	N/A	
<b>Ambient Temperature (°C):</b>	25.0	
<b>Stabilization Time (Hours):</b>	0:45	
<b>Total Operating Time (Hours):</b>	1:55	





FIG. 1 LUMINAIRE

\*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.




**CRI & CCT**

x	0.4336
y	0.4040
u'	0.2485
v'	0.5209
CRI	82.50
CCT	3056
Duv	0.00044

**R Values**

R1	81.12
R2	92.00
R3	94.98
R4	80.23
R5	81.58
R6	90.63
R7	81.84
R8	57.59
R9	4.65
R10	82.16
R11	80.02
R12	72.61
R13	83.86
R14	97.78



\*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

### Temperature test

Per client's request, a thermocouple is placed on the back of the LED board (FIG. 2). Thermocouple temperature is measured after the fixture is stabilized.

**Thermocouple Temperature (°C): 58.1**



FIG. 2 Thermocouple location

## Test Methods

### Spectral Measurements - Integrating Sphere

A Sensing Spectroradiometer SPR-3000, in conjunction with Light Laboratory 2 meter integrating sphere was used to measure total photosynthetic photon flux (PPF), chromaticity coordinates, correlated color temperature(CCT) and the color rendering index(CRI) for each sample.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

#### Disclaimers:

This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST or any agency of Federal Government.

Report Prepared by : Keyur Patel

Test Report Released by:



Jeff Ahn  
Engineering Manager

Test Report Reviewed by:



Steve Kang  
Quality Assurance