



Fast & compact for improved efficiency.

The Panasonic KV-S1026C scanner features a slim and compact body, ideal for business use where space is limited, and offers easy operation with advanced features.



Features

- High-speed scanning up to 30ppm / 60ipm
- 50 Sheet Automatic Document Feeder
- Slim, compact body (W 303 mm x D 177 mm x H 137 mm)
- 3 customisable Single Touch Scan Keys
- Active Double Feed Prevention Roller System
- Simple Touch Free Scanning
- Embossed Card Scanning
- Includes Panasonic Image Capture Plus Software

Fast**High-Speed Scanning**


Routine scanning is quick and easy. Scan through mountains of documents and large amounts of daily forms, quickly and effortlessly converting them into digital data.

**30/60 ppm/ipm****Easy****Single Touch Scan**

Simply press one of the preset buttons to send scan data straight to a destination of your choice.

**Reliable****Active Double Feed Prevention**

The reverse separating roller moves the second and following pages backward to reduce the occurrence of double feeding.

**Specifications**

| | | |
|--|--|---|
| SCANNER TYPE | Duplex Sheet Feed Scanning | |
| SCANNER TECHNOLOGY | 1-Line CIS (Contact Image Sensor) | |
| SCANNING SPEED*1 (A4, Portrait) | Up to 30 ppm / 60 ipm (Binary 200 dpi) Up to 20 ppm / 40 ipm (Colour 200 dpi) | |
| RESOLUTION (Colour and B/W) | Resolution : 100 - 600dpi (1dpi step) Optical : 300/600dpi | |
| AUTOMATIC DETECTION | Ultrasonic Double Feed Detection | |
| IMAGE COMPRESSION | JPEG (Grayscale/Colour) | |
| IMAGE OUTPUT | Binary, Grayscale, Colour, MultiStream (Colour & Binary or Gray & Binary) | |
| BINARY MODE HALFTONE | Dither, Error Diffusion | |
| IMAGE CONTROL | Automatic Binary/Color Distinction, Multi Color Drop Out, Blank Page Removal, Double Exposure, Smooth Background, Automatic Cropping, De-skewing, Dynamic Threshold, White Level From Paper, Image Emphasis (5 steps), Gamma Correction, Automatic Separation, Noise Reduction, Shadow Removal, Mirror Image, Monochrome Reversing, 2-Page Separation and much more. | |
| OTHER FUNCTIONS | Zone OCR (a function of the Image Capture Plus software that adds characters from the document to the output file name), Separation sheet, Single Touch Scan, Skip key | |
| DOCUMENT | SIZE (ADF) | Minimum 48 mm x 70 mm (1.9 in. x 2.8 in.) length Maximum 216 mm x 2,540 mm (8.5 in. x 100 in.) length |
| | WEIGHT/THICKNESS*2 | Single 20 - 209 g/m ² (5.4 lbs. - 55 lbs.) Continuous 20 - 209 g/m ² (5.4 lbs. - 55 lbs.) Card Up to approx. 0.76 mm (0.03 in.) in thickness + embossing (ISO standard 7810 ID-1 card scanning including embossed card) |
| FEED TRAY CAPACITY | Up to 50 sheets (20 lbs., 80 g/m ²), 3 hard cards (ISO 7810 ID-1) | |
| SUPPORTED OPERATING SYSTEM | Windows® XP SP3 or later (32-bit), Windows Vista® SP2 or later (32/64-bit), Windows® 7 and Windows® 8 (32/64-bit), Windows® 10 (32/64-bit) | |
| INTERFACE | High-Speed USB 2.0, Up to 480 Mbps transfer rate | |
| POWER REQUIREMENT | AC 100 - 120 V 50/60 Hz, AC 200 - 240 V 50/60 Hz | |
| POWER CONSUMPTION | Scanning mode 17 W or less Idle mode 4.5 W or less Sleep mode 1.6 W or less Power off mode 0.3 W or less | |
| OPERATING ENVIRONMENT | Temperature 10 °C - 35 °C (50 °F - 95 °F) Humidity 20 % RH - 80 % RH | |
| STORAGE ENVIRONMENT | Temperature 0 °C - 40 °C (32 °F - 104 °F) Humidity 10 % RH - 80 % RH | |
| EXTERNAL DIMENSIONS*3 (W x D x H) | 303 mm x 177 mm x 137 mm (11.9 in. x 7 in. x 5.4 in.) without Feed tray | |
| WEIGHT*3 | 2.7 kg (5.9 lbs.) | |
| ACCESSORIES | DVD-ROM : Drivers and Utilities for Windows / Manuals Driver software ISIS / TWAIN / WIA Application software Image Capture Plus Safety Guide, Quick Reference Guide, Mixed batch card guide, AC adapter & Power cord, USB cable | |
| OPTIONS | ROLLER EXCHANGE KIT | KV-SS058 (Double-feed prevention roller x 1, Paper feed roller x 1) |
| | ROLLER CLEANING PAPER | KV-SS03 |
| | FLATBED SCANNER | KV-SS081 |

Dimensions

As an ENERGY STAR® partner, Panasonic has determined that this product* meets the ENERGY STAR guidelines for energy efficiency.



*1 The scanning speed differs depending on the host computer, the operating system, the application, the measuring method, the quantity of data in the image, and the paper type. The scanning speed depends on a measuring method of Panasonic.

*2 "Weight in pounds" of paper represents the weight of 500 (432 x 559 mm / 17 x 22 inches) sheets.

*3 Dimensions and weight are approximate.

Trademarks and registered trademarks

- ENERGY STAR and the ENERGY STAR mark are registered U.S. marks.
- ISIS is a registered trademark or trademark of Open Text Corporation.
- Microsoft®, Windows® and Windows Vista® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- All other brand or product names are the property of their respective holders.

• Design and specifications are subject to change without notice.

This Product is designed to reduce hazardous chemical substances along with the RoHS directive.

DISTRIBUTED BY :

PanasonicDocument Scanner: <https://panasonic.net/cns/office/products/scanner/>

Printed in Japan MG-SCN003EN 1908NSP/FP-U3