



## PANASONIC KV-S2087 A4 COLOUR SCANNER

### EXCEPTIONAL CAPABILITIES, EXCEPTIONAL COST

The brand-new KV-S2087 high-speed, multi-document A4 colour scanner brings you all the flexibility and efficiency of enhanced time-saving features without the prohibitive costs.

With its exceptional extended functionality and competitive price, the KV-S2087 is the new must-have for medium and large-sized businesses across the finance, legal, healthcare and hospitality industries.

#### Key features

- Incredibly fast scanning speed of 85ppm/ 170 ipm in duplex\*
- One-touch scanning of up to 200 documents in ADF
- Passport, card and long paper scanning
- U-turn and straight feeding path
- Digital imprinter and post imprinter
- Remote control software for online scanning status checks
- Auto Rescan and Auto Preview features
- Compact 343 x 315 x 260 dimensions
- Extended roller life of 350k sheets

# PRODUCT GUIDE AND SPECIFICATIONS



ITEMS		KV-S2087
Scanning face	-	Duplex
Scanning method	-	Colour CIS (600 dpi step), Black or White Background
Scanning resolution	-	100 - 600dpi (1dpi step) and 1,200dpi (interpolated) Optical: 300 dpi / 600 dpi (Automatic switch)
Scanning speed	Binary/colour - Simplex	Up to 85 ppm
-	A4 or letter size 200/300 dpi - Duplex	Up to 170 ipm
Double feed detection	-	Ultrasonic (The length of document that can be detected is 70mm or more)
Image compression	-	MH, MMR (Software ICP), JPEG
Binary mode halftone	-	Dither, Error Diffusion
Image control	-	Auto preview, Auto rescan, Automatic Brightness Adjustment, Multi Colour Drop Out, Dynamic Threshold, White Level From Paper, Image Emphasis Gamma, Automatic Separation, Noise Reduction
Other functions	-	Length Control, Barcode detection, Patchcode Detection (Type 2, 3, T), Control Sheet detection, Long Paper, Double Feed Skip
Documents	Width	48mm - 216mm (1.9 in. - 8.5 in.)
-	Length	Automatic feeding: 70 mm - 356 mm (2.75 in. - 14 in.) Manual feeding: 70 mm - unlimited (2.75 in. - unlimited)
-	Thickness	0.04 mm - 0.66 mm (1.6 mils - 25.98 mils) Note 1 mil = 0.001 in.
-	Weight	U-turn path (front exit): 20 g/m <sup>2</sup> - 157 g/m <sup>2</sup> (5.2lb. - 42lb.) Straight path (rear exit): Automatic feeding: 20g/m <sup>2</sup> - 157 g/m <sup>2</sup> (5.2lb. - 42lb.) Manual feeding: 20 g/m <sup>2</sup> - 546 g/m <sup>2</sup> (5.2lb. - 145lb.)
Card	Format	ISO format
-	Size	85.6mm x 54mm (3.4 in. x 2.1 in.)
-	Thickness	0.76mm (0.03 in.)
Feed tray capacity	-	200 sheets: 80 g/m <sup>2</sup> (21 lb.) High-quality woodfree paper
Supported operating system	-	Windows® XP SP3 (32bit/64bit), Windows Vista® SP2 (32bit/64bit), Windows® 7 (32bit/64bit), Windows® 8 (32bit/64bit), Windows® 8.1 (32bit/64bit) Windows® 10 (32bit/64bit), Windows Server® 2003 SP2 (32bit/64bit) Windows Server® 2003 R2 SP2 (32bit/64bit), Windows Server® 2008 SP2 (32bit/64bit) Windows Server® 2008 R2 SP1 (64bit), Windows Server® 2012 (64bit)
Interface	-	USB 3.0 interface Note: If the scanner is connected to a USB hub, it is not guaranteed to work.
External dimensions (W x D x H)	-	350mm x 319mm x 242mm (13.78 in. x 12.56 in. x 9.53 in.) *Protruding parts not included
Weight	-	9.0kg (19.84 lbs)
Power requirement*	-	AC100 - 127V, 50/60Hz, 1.2A AC100 - 240V, 50/60Hz, 1.2 - 0.7A AC220 - 240V, 50/60Hz, 0.7A
Power consumption	Maximum (scanning)	65W or less
-	Minimum (ready)	20W or less
-	Sleep	3.0W or less
-	Power off	0.5W or less
Operating environment	-	Temperature: 5°C - 35°C (41°F - 95°F) Humidity: 20% - 80% RH
Storage environment	-	Temperature: -10°C - 50°C (14°F - 122°F) Humidity: 8% - 75% RH
Accessories	-	CD-ROM: Device Driver, ISIS driver software, TWAIN driver software User utility, Scan Button Setting Tool, Image Capture Plus with the OCR Engine Operating Manual, Control data sheet (PDF) Quick Installation Guide, Power Cord, USB Cable (1.5m (59 in.) / USB3.0)
Options	Roller exchange kit	KV-SS063
-	Roller cleaning paper	KV-SS03
-	Imprinter unit (Post)	KV-SS020
-	Ink cartridge	KV-SS021
-	Carrier sheet	KV-SS076
-	Flatbed scanner	KV-SS081

This product is designed to reduce hazardous chemical substances in accordance with the RoHS directive.

The power requirement differs depending on the country/area. All photographs in this brochure are simulated. Weights and dimensions are approximate. Specifications are subject to change without notice. These products may be subject to export control regulations. Bound documents can be scanned by setting the manual feed selector to manual scanning (Manual) and the Paper path selector to straight path (rear exit).

You can use an optional carrier sheet (KV-S2076) to scan booklet using manual scanning and straight path (rear exit).

ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. ISIS is registered trademark or trademark of EMC Corporation in the United States and other countries. Windows, Windows Vista and Windows Server are either registered trademarks or trademark of Microsoft Corporation in the United States and/or other countries. All other brand or product names are the property of their respective holders.

**Panasonic**  
BUSINESS