






UR94 Baltic





UR27 Safari







UR51 Crater



























UR17 Storm

Contourett

Application

Seating

Content

100% Polyurethane

Width

54"

Weight

20.3 ounces per linear yard

Finish

Silver-based ion technology

Backing

70% Polyester, 30% Cotton

Abrasion

200,000 double rubs (W)

Flame Resistance

NFPA 260 (UFAC Class 1), California TB 117-2013 compliant

Manufacturer

HON

Maintenance

• For wet spills, gently blot with dry cloth to remove spill.

- For dried spills, gently work the spill in a non-aggressive circular motion using a damp cloth, making sure to not oversaturate the fabric.
- For dried stains, use a mixture of Tide or Oxiclean and warm water (1 teaspoon of soap for every 16 ounces of water). Follow instructions for dried spills above. Make sure to wipe away any excess soap left behind and remove any moisture with a dry cloth.
- $\bullet \ \, \text{For non-liquid spills, always remove excess contaminant from surface before cleaning. The use of a soft brush } \\$ or soft abrasive can be used to remove dried contaminants before performing liquid cleaning.
- For healthcare-related stains, a water-to-bleach solution of 5:1 is recommended. Rinse cleaned area with water.
- For stains requiring the use of solvent, spray the solvent directly onto the stain and allow it to sit for 2-3 minutes, avoiding oversaturating the fabric. Follow directions for dried stains above.
- Always allow fabric to air dry.

ACT Registered Certification









Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan