

FEATURES & SPECIFICATIONS

POLE - The pole shaft is fabricated from hot rolled carbon steel having a minimum yield of 47,000 PSI and conforms to ASTM A500 grade B requirements. 10 to 30 feet mounting heights can be used most of parking lots.

ANCHOR BOLTS - The anchor base is fabricated from a structural quality hot rolled carbon steel plate with minimum yield strength of 55,000 PSI and fully galvanized.

BASE BOLT COVER - Two-piece standard base cover is provided which encapsulates the base plate, heavy gauge quality carbon steel and pretreated with corrosion inhibitors.

FINISH - Four stage metal pretreatment processes and sealers provide maximum corrosion resistance. Polyester powder coat finish is baked for supreme endurance durability and hardness.

Maximum EPA

70 mph	15.2
80 mph	12.5
90 mph	10.1
100 mph	8.5
110 mph	6.9
120 mph	5.4

Technical Data

Pole Height	15ft
Wall Gauge	11 Gauge
Shaft Dimensions	4" x 4"
Bolt Circle	8.27" - 11.42"
Bolt Size	3/4" x 17" x 3"
Base Size	11"
Est. Shipping Weight	117 lbs

Mounting Drilled



D 1	
D 2 - 90°	
D 2 - 180°	
D 3 - 90°	
D 4 - 90°	

Tenon Mount



2 1/2" OD Tenon

Drilled Mount



ORDERING INFORMATION

Series	Pole Height	Pole Size	Pole Gauge	Color	Mounting
SSS	15 (15 ft)	4 (4" Square)	11 (11 Gauge)	B (Bronze)	2 1/2" OD Tenon