



Dimensions: $\Phi 16\frac{1}{4} \times 8$ "

Weight: 17 lbs

ORE Lighting

HBL 200w Highbay

Watts: 200W

Type: V

Color Temp: 5000K (Cool)

CRI: 71

L70: Lifespan: 100,000

Lumens: 30000

Listings

UL Listing:

Suitable for wet locations

DLC Listed:

This product is on the DESIGN Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.

IESNA LM-79 & LM-80 Testing:

ORE LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

Electrical

Driver:

One Driver, Constant Current, Class I with 10 KV surge, 100-277V, 50-60Hz, Power Factor 99%, IP67

THD:

20% at 100-277V. 10% at 220-240V.

Surge Protection:

6kV line-line, 10kV line-earth.

LED Characteristics

Lifespan:

100,000 – hour LED lifespan based on IES LM-80 results and TM-21 calculations.

LEDs:

Multi-chip, high-output, long-life LEDs

Color Temp:

From 3000k (Warm), 4000k (Neutral) to 5000k (Cool)

Color Uniformity:

ORE's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products.

Construction

IES Classification:

The Type V distribution is ideal for general indoor warehouses and sport applications.

Maximum Ambient

Operating Temperature:

-40°C to +55°C (-104°F - +131°F)

Cold Weather Starting:

Minimum starting temperature is -40°C (-104°F)

Thermal Management:

Superior thermal management with external "Air-Flow" fins, nature transfer heat skin design.

Lens:

Tempered glass lens

Housing:

Precision die-cast aluminum housing, tempered glass

IP Rating:

Ingress Protection rating of IP66 for dust and water

Gaskets:

High-temperature silicone gaskets

Finish:

Formulated for high-durability and long-lasting color

Green Technology:

Mercury and UV-free. RoHS compliant components. Polyester powder coat finish formulated without the use of VOCs or toxic heavy metals.

Other

Replacement:

Replaces above 750W Metal Halide

Warranty:

ORE warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. 10 Year Warranty available upon request.

Information and Help Contact: 346-874-7955 Email: sales@orelighting.com Website: www.orelighting.com

Note: Specifications are subject to change at any time without notice