



ORE LIGHTING INC.

13000Murphy Road, Suite 116, Stafford, Houston, Texas 77477 Website: www.orelighting.com

Tel: 346-874-7955, 346-874-7952 E-mail: info@orelighting.com or leon@orelighting.com

Philips LuminLeds 3030 SMD.ORE-GSL100 Gas station Light Specifications

Model	ORE-GSL100	Picture
System power	100W±10%	
Fixture Material	Die-cast aluminum alloy	
Light source	Philips LuminLeds 3030	
Color Temperature	3000K~5000K±300K	
CRI	≥70	
Light distribution standard	(IESNA standards)	
Driver	INVENTRONICS(0-10V / PWM Intelligent Dimming)	
Input voltage	90-305VAC	
Output voltage	42VDC (22V~61V)	
Output current	2900mA	
Frequency range	47-63Hz	
Power factor	PF > 0.98. 115VAC; PF > 0.96. 230VAC	
Power-supply efficiency	>90%	
Luminous efficacy class	LER > 120 lm/W	
Protection	Short circuit/Over voltage/Over temperature automatic protection	
Operating temperature	-40℃~+55℃	
Operating humidity	10~95% RH	
Protection level	IP66 or Wet	
Heat-dissipating method	Natural air cooling	
Installation angle	0°(0-90 ° adjustable)	
Safety certification	ETL, DLC,FCC, IP66	
Size	11"×11"×10"	
Net weight	11lbs	
Packaging	Carton + polyfam	