



ORE LIGHTING INC.

13000Murphy Road, Suite 116, Stafford, Houston, Texas 77477 Website: www.orelighting.com

Tel: 346-874-7955, 346-874-7952 E-mail: info@orelighting.com or leon@orelighting.com

Philips LuminLeds 3030 SMD.ORE-GSL120 Gas station Light Specifications

| Model | ORE-GSL120 | Picture |
|-----------------------------|--|---|
| System power | 120W±10% |  |
| Fixture Material | Die-cast aluminum alloy | |
| Light source | Philips LuminLeds 3030 168PCS | |
| Color Temperature | 3000K~5000K±300K | |
| CRI | ≥70 | |
| Light distribution standard | (IESNA standards) | |
| Driver | INVENTRONICS(0-10V / PWM Intelligent Dimming) | |
| Input voltage | 90-305VAC | |
| Output voltage | 42VDC (22V~61V) | |
| Output current | 2900mA | |
| Frequency range | 47-63Hz | |
| Power factor | PF > 0.98. 115VAC; PF > 0.96. 230VAC | |
| Power-supply efficiency | >90% | |
| Luminous efficacy class | LER > 120 lm/W | |
| Protection | Short circuit/Over voltage/Over temperature automatic protection | |
| Operating temperature | -40℃~+55℃ | |
| Operating humidity | 10~95% RH | |
| Protection level | IP66 or Wet | |
| Heat-dissipating method | Natural air cooling | |
| Installation angle | 0°(0-90 ° adjustable) | |
| Safety certification | ETL, DLC,FCC, IP66 | |
| Size | 15"×15"×10" | |
| Net weight | 12.5lbs | |
| Packaging | Carton + polyfam | |