



ORE LIGHTING INC.

13000Murphy Road, Suite 116, Stafford, Houston, Texas 77477 Website: www.orelighting.com

Tel: 346-874-7955, 346-874-7952 E-mail: info@orelighting.com or leon@orelighting.com

Philips LuminLeds 3030 SMD.ORE-WPL45 Wallpack Specifications

Model	ORE-WPL45	Picture
System power	45W±10%	
Fixture Material	Die-cast aluminum alloy & PC lens	
Light source	Philips LuminLeds 3030	
Color Temperature	3000K~5000K±300K	
CRI	≥70	
Light distribution standard	(IESNA standards)	
Driver	SOSEN LED DRIVER	
Input voltage	90-305VAC	
Output voltage	30~36VDC	
Output current	1250mA	
Frequency range	47-63Hz	
Power factor	PF > 0.98. 115VAC; PF > 0.96. 230VAC	
Power-supply efficiency	>91%	
Luminous efficacy class	LER>110 lm/W	
Protection	Short circuit/Over voltage/Over temperature automatic protection	
Operating temperature	-40℃~+55℃	
Operating humidity	10~95% RH	
Protection level	IP66 or wet	
Heat-dissipating method	Natural air cooling	
Installation angle	Close to the wall with the angle unadjustable	
Safety certification	ETL, DLC,FCC	
Size	14¼"×7½"×9¼"	
Net weight	7.4lbs	
Packaging	Carton + polyfam	