



## WPL 75w Wallpack

**Watts: 75W**

**Type: III**

**Color Temp: 5000K (Cool)**

**CRI: 71**

**L70: Lifespan: 100,000**

**Lumens: 9650**

### Listings

#### **UL Listing:**

Suitable for wet locations

#### **DLC Listed:**

This product is on the DESIGN Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.

#### **IESNA LM-79 & LM-80 Testing:**

ORE LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

### Electrical

#### **Driver:**

One Driver, Constant Current, Class I with 10 KV surge, 100-277V, 50-60Hz, Power Factor 99%, IP67

#### **THD:**

20% at 100-277V. 10% at 220-240V.

#### **Surge Protection:**

6kV line-line, 10kV line-earth.

### **LED Characteristics**

#### **Lifespan:**

100,000 – hour LED lifespan based on IES LM-80 results and TM-21 calculations.

#### **LEDs:**

Multi-chip, high-output, long-life LEDs

#### **Color Temp:**

From 3000k (Warm), 4000k (Neutral) to 5000k (Cool)

#### **Color Uniformity:**

ORE's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products.

### Construction

#### **IES Classification:**

The Type III distribution is ideal for general outdoor wall mounted parking lot and security lighting.

#### **Maximum Ambient**

#### **Operating Temperature:**

-40°C to +55°C (-104°F - +131°F)

#### **Cold Weather Starting:**

Minimum starting temperature is -40°C (-104°F)

#### **Thermal Management:**

Superior thermal management with external "Air-Flow" fins, nature transfer heat skin design.

#### **Housing:**

Precision die-cast aluminum housing, tempered glass

#### **IP Rating:**

Ingress Protection rating of IP66 for dust and water

#### **Gaskets:**

High-temperature silicone gaskets

#### **Finish:**

Formulated for high-durability and long-lasting color

#### **Green Technology:**

Mercury and UV-free. RoHS compliant components. Polyester powder coat finish formulated without the use of VOCs or toxic heavy metals.

### Other

#### **Replacement:**

Replaces above 150W Metal Halide

#### **Warranty:**

ORE warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. 10 year warranty provided upon request.

FAMILY	OPTICS	WATTAGE	CCT	VOLTAGE	MOUNTING	FINISH
<b>WPL</b>	Type III <b>T3</b> Type IV <b>T4</b>	75W <b>75</b> 100W <b>100</b> 150W <b>150</b>	<b>3K</b> 3000K Warm <b>4K</b> 4000K Neutral <b>5K</b> 5000K Cool	120-277V <b>MT</b> 480V <b>480V</b>	Wall Mount <b>Blank</b>	Bronze <b>Blank</b> Aluminum Silver <b>AS</b> Black <b>BK</b>