



## HYDRAULIC TILTER QUOTATION WORKSHEET

Company \_\_\_\_\_ Date \_\_\_\_\_  
 Contact \_\_\_\_\_ Quote Due \_\_\_\_\_ Desired Delivery \_\_\_\_\_  
 Phone No.: \_\_\_\_\_ Contact Email: \_\_\_\_\_ State \_\_\_\_\_  
 Omni Sales Contact: \_\_\_\_\_ Quote #: \_\_\_\_\_  
 Quantity: \_\_\_\_\_

### APPLICATION INFORMATION

How is tilter to be used? \_\_\_\_\_  
 \_\_\_\_\_

Equipment mounted to the tilter: \_\_\_\_\_

Product Description: \_\_\_\_\_

Size: \_\_\_\_\_ W x \_\_\_\_\_ L x \_\_\_\_\_ H, WT = \_\_\_\_\_ LBS.

#### Tilter Information:

Capacity: \_\_\_\_\_ Platform Length: \_\_\_\_\_ Platform Width: \_\_\_\_\_

**Height Info.:** Lowered \_\_\_\_\_  
 Degree of Tilt \_\_\_\_\_ (0°- 60°)

**Cycle Info.:** Jogs/Cycle \_\_\_\_\_  
 Cycles/Hour \_\_\_\_\_

#### Power Unit:

- External
- Internal
- None

#### Plant Voltage:

- 110V Single Phase
- 220V Single Phase
- 220V Three Phase
- 440V Three Phase
- 208V Single Phase
- 575V Three Phase

#### Controls:

- Foot Pedal
- Hand Held Pendant
- No Controller
- Less All Controls

#### How is tilt loaded?

- End
- Side

#### How is tilt off loaded?

- End
- Side

#### Options:

- Skirting
- Stainless

#### Lip on Hinged End:

(Standard is 8 in.)

- Yes
- No
- Other \_\_\_\_\_

Other: \_\_\_\_\_

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Approval Drawing Required:  Yes  No