

Approval Drawing Required: ☐ Yes ☐ No

AID Equipment (Salt Lake City, UT branch) Phone: 801.566.2112 Sales@aideq.com www.aideq.com

24V MOTOR DRIVEN ROLLER CONVEYOR QUOTATION WORKSHEET

Company	Date
Contact	Quote Due Desired Delivery
	Contact EmailState
	Quote #:
Quantity	
<u></u>	
Product Specs:	Roller Specs:
Max:	1.9 in. dia. x 16 ga. Galv.
- Width (inches): Length (inches):	Ocation:
- Height (inches):Weight (lbs):	
Min:	
- Width (inches): Length (inches):	Support Type: Quantity:
- Height (inches):Weight (lbs):	
Description:Weight (ibs)	9 11
Max. Qty.: Total Live Load:	
Temperature	Application type:
•	☐ Transportation☐ Zero Pressure - Zone Length
-Environment: -Product:	
-r 10ddct	
Conveyor Construction: Between Frame (BF) Roller C/C Straight Length: Curve - Degree: Inside Radius (I.R.): Bolt-Together	
Plant Voltage: ☐ 110V Single Phase ☐ 220V Single Phase ☐ 220V Three Phase Speed: ☐ 575V Three	Phase
☐ FixedFPM ☐ VariabletoFPM	
→ variabletoFPIVI	
Drive Bands:	
☐ Standard 83A (50 lbs. Capacity)	Notes:
☐ High Tension 85A (100 lbs. Capacity)	
☐ Other	