



COMPLETE VARIABLE SPEED SOLUTION



FEATURES:

- Variable V/Hz & open loop flux vector frequency drive
- L-style mounting bracket, 8 ga. galvanized
- 10' Pre-wired - 12AWG min. motor cable
- 10' Pre-wired - 12AWG min. power cord
- Cord grips for strain relief
- NEMA 1 enclosure standard

Advantages:

- Easy installation
- Soft start/stop
- Simple setup
- Low cost
- Quick ship
- Basic parameter list sticker
- Front panel reverse button with lockout capability
- Optional remote start/stop packages available
- Single phase input produces 230VAC 3 PHASE out



Input Voltages:

- 115 VAC 1 PHASE
- 208 VAC 1 PHASE
- 230 VAC 1 PHASE
- 208 VAC 3 PHASE
- 230 VAC 3 PHASE
- 460 VAC 3 PHASE
- 575 VAC 3 PHASE

Horsepower:

- 1/4 TO 1 HP
- 1/4 TO 3 HP
- 1/4 TO 3 HP
- 1/4 TO 5 HP
- 1/4 TO 5 HP
- 1/4 TO 5 HP
- 1/4 TO 5 HP

Options:

- NEMA 4x/12 enclosure
- 7 1/2 HP available
- 10 HP available



AID Equipment
 (Salt Lake City, UT branch)
 Phone: 801.566.2112
 Sales@aideq.com
 www.aideq.com