

AID Equipment (Salt Lake City, UT branch) Phone: 801.566.2112 Sales@aideq.com www.aideq.com

## PLASTIC BELT CONVEYOR QUOTATION WORKSHEET

Approval Drawing Required:  $\square$  Yes  $\square$  No

Company	Date
Contact	Quote Due Desired Delivery
Phone No.:	Contact Email:State
Omni Sales Contact:	Quote #:
Quantity:	
Product Specs:	Modular Plastic Belt Specs:
Max:	Belt Width: Inches Belt Style:
- Width (inches): Length (inches):	
- Height (inches):Weight (lbs):	Application Design Needs:
Min:	☐ Stainless Steel Wash Down ☐ Sanitary
- Width (inches): Length (inches):	Other
- Height (inches):Weight (lbs):	(For Help: www.omni.com/products/ss/index.html)
Description:	
Max. Qty.: Total Live Load*:	Product Enters By:
Temperature	☐ Conveyed On ☐ Fork Truck
-Environment:	
-Product:	Product Exits By:
☐ Wet ☐ Dry ☐ Other	☐ Conveyed off ☐ Fork Truck
Conveyor Construction:	☐ Robot ☐ Other
☐ Welded	- Quantity of Starts and Stops per Day
☐ Painted ☐ Epoxy Painted	- *Will the Conveyor be started with a load??
Powder Coated Color RAL:	☐ Yes ☐ No ☐ Soft Start Required?
☐ Stainless Steel	Support Type:
Mill Finish  Polished	Legs Ceiling Supports
☐ Bolt-Together Galvanized	None Top of Belt:
Bed Type:  Slider Bed  Open Style Slider	der Bed
Conveyor Orientation:	*Speed:
☐ Horizontal ☐ Incline ☐ Decline	Fixed (FPM)
A ='" Horizontal Overall Length	☐ Variable Low Speed (FPM)
•	High Speed (FPM)  ☐ AC Speed Controller ☐ DC Speed Controller
B ='" Top of Belt	AC Speed Controller
C ='" Top of Belt	Drive Type:
D =': Elevation Change	Under Hung  Shaft Mount  Side Mount
E ='" Degree (Approx.)	Drive Location:
	☐ Discharge End ☐ Center
A — A	ŭ
• • • • • • • • • • • • • • • • • • • •	Plant Voltage:
	☐ 110V Single Phase ☐ 460V Three Phase
B L	☐ 220V Single Phase ☐ 208V Three Phase
Li	☐ 220V Three Phase ☐ 575V Three Phase
	Other
☐ Curve:" Inside Radius	Other:
Degree of Curve 45 90 180 Oth	ner
Curve tangent typically (2x) the belt width. (Mini	
	conveyors are fully loaded and require soft starts.