

AID Equipment (Salt Lake City, UT branch) Phone: 801.566.2112 Sales@aideq.com www.aideq.com

SLAT CONVEYOR QUOTATION WORKSHEET

Approval Drawing Required: \Box Yes \Box No

Company		Date
Contact		
Phone No.	Contact Email	State
Omni Sales Contact		Quote #:
Quantity		
Model: ☐ Slat 200 ☐ Slat 300	☐ Slat 400	
Drive provided by: ☐ Customer ☐ Omni	Chain Pitch:in	
Speed (fpm): (30 std)	Slat Gauge: ga	
☐ Fixed	Conveyor Length:	Product Width: in.
Variable	Minimum Stable	Product Weight: lbs.
AC Controller	Slat Lengthft.	Is the product palletized?
DC Controller	Integral Number of	ves no
□ Brand	Work Zonesin	. 9 Block Pallet
110V Single Phase	Maximum OAL	Dellat Described (Olat
220V Single Phase	of Conveyorft.	□ Pallet Runners Perpendicular
☐ 220V Three Phase		to Slats
440V Three Phase		
□ 208V Three Phase	Description of Product:	
☐ 575V Three Phase		
Fixtures (if required): Qty. of Fixtures:	How is the Broduct Loaded?	
Fixtures provided by: ☐ Customer ☐ Omni		
Fixture Length: in.		
Fixture Width: in.	How is the Product Unloaded?	
Fixture Height: in.		
Fixture Weight: lbs.		
Fixture Centers: in.		
Total Live Load:lbs.	6.0	51.004
Top Of Slat:in.	[M]	← FLOW
Options: 4" Chain	☐ Paint Options:	_
☐ Type of Chain☐ PVC Edge Guards	☐ Painted ☐ ☐ Conveyor Color	Epoxy Painted 🖵 Powder Coated
☐ End Guards (Sheet Metal/Expand		
□ Skirting Guard□ Flat Head Cap Screws		
☐ Side Guides in.	☐ Controls W	ViredLooseBy Customer
☐ Clutch		
☐ Brake		