



PRODUCT STACKER/DESTACKER QUOTATION WORKSHEET

Company _____ Date _____
 Contact _____ Quote Due _____ Desired Delivery _____
 Phone No. _____ Contact Email _____ State _____
 Omni Sales Contact _____ Quote #: _____
 Quantity _____

Operation:

- Stack
- Destack
- Both

Environment:

- Dry Wet Washdown
- Cold/Hot Dirty
- Other: _____

Configuration:

- Straight Thru
- 90 Degree Left Hand
- 90 Degree Right Hand

Pneumatics: (Parker)

- Cylinders Mounted Only
- Cylinders Mounted & Plumbed to Valves
- Cylinders Mounted & Plumbed to Valve Board with Filter/Regulator & Safety Lockout

Lifting Mechanism:

- Pneumatic Cylinder
- Hydraulic Scissor Lift
- Mechanical Ball Screw

Plant Voltage:

- 110V Single Phase 460V Three Phase
- 220V Single Phase 208V Three Phase
- 220V Three Phase 575V Three Phase

Fork Mechanism:

- Pneumatic Cylinder
- Hydraulic Cylinder
- Other: _____

Control Voltage:

- 120V/1PH/60HZ
- 24V DC
- Other: _____

Product Size: (In Direction of Travel)

Length: _____ Width: _____
 Height: _____ Weight: _____
 # of Products: _____ Stack Height: _____
 Products per Minute: _____
 Products per Hour: _____
 Product: _____
 (Pallet, Rack, Tire, Tote, Other)
 Material: _____
 (Wood, Plastic, Steel, Other)

Electrical: (Allen-Bradley)

- None
- Sensors for Product & Machine Position Mounted and Wired to J-Box
- Control Panel with PLC Logic & Sensors Mounted and Wired

Integral Conveyor:

- Chain Driven Live Roller Chain Conveyor
- By Others

Infeed:

Conveyed In Fork Truck Load
 Elevation: _____ Speed: _____

Other: _____

Discharge:

Conveyed Out Fork Truck Unload
 Elevation: _____ Speed: _____

Finish:

- Standard Enamel Paint Epoxy Paint
- Stainless Steel Other: _____

Approval Drawing Required: Yes No