



TURNTABLES QUOTATION WORKSHEET

Company _____ Date _____
 Contact _____ Quote Due _____ Desired Delivery _____
 Phone No. _____ Contact Email _____ State _____
 Omni Sales Contact _____ Quote # _____
 Quantity: _____

Product Specs:

Max:
 - Width (inches): _____ Length (inches): _____
 - Height (inches): _____ Weight (lbs): _____
 Min:
 - Width (inches): _____ Length (inches): _____
 - Height (inches): _____ Weight (lbs): _____
 Description: _____
 Max. Qty.: _____ Total Live Load: _____
 Temperature
 -Environment: _____
 -Product: _____

Turntable Construction:

Welded
 Painted Epoxy Painted
 Powder Coated Color RAL: _____
 Diameter of Table: _____
 Top of Table: _____
 Top of Roller: _____
 Capacity: _____
 Bearing Support
 Cam Follower Roller Turn Roller
 Rotary Bearing Yoke Roller

Powered Turntable Specifications:

Rotation:
 90 Deg. 180 Deg. 270 Deg. 360 Deg.
 Other: _____
 Time for Specified Rotation: _____
 Method of Drive:
 Sprocket and Chain
 Other: _____

Plant Voltage:

110V Single Phase 460V Three Phase
 220V Single Phase 208V Three Phase
 220V Three Phase 575V Three Phase

Transition Rollers:

Gravity Rollers Power Rollers

Approval Drawing Required: Yes No

Manual Turntable Specifications:

Rotation:
 90 Deg. 180 Deg. 270 Deg. 360 Deg.
 Other: _____
 Detents: Yes No

Low Profile Manual Turntable (LPMT) Specifications:

Rotating Deck Size: (Capacity)
 (2000#) 24" Square 36" Square 48" Square
 (4000#) 24" Square 36" Square 48" Square
 (LPMT) Options:
 Detent Stops @ 90 Degrees (Spring) Not Locking
 Detent Hand Release @ 90 Degrees
 Detent Foot Release @ 90 Degrees
 Circular Table Platform Stand
 Cross Bracing (Above 30" T.O.T.)

Note: NOT Recommended for use with conveyor because of offset loading.

Options:

Table Position Sensing: Mounted Only
 Mounted and Wired
 Voltage: _____
 Limit Switch: _____
 Proximity Switch: _____
 Slip Ring (Y/N) 8-Pole Standard Mounted and
 Wired: _____
 (Slip Ring maybe required over 270 degrees)

Notes: _____

