



## WIRE MESH CONVEYOR QUOTATION WORKSHEET

Company \_\_\_\_\_ Date \_\_\_\_\_  
 Contact \_\_\_\_\_ Quote Due \_\_\_\_\_ Desired Delivery \_\_\_\_\_  
 Phone No.: \_\_\_\_\_ Contact Email: \_\_\_\_\_ State \_\_\_\_\_  
 Omni Sales Contact: \_\_\_\_\_ Quote #: \_\_\_\_\_

Quantity: \_\_\_\_\_

### Product Specs:

Max:  
 - Width (inches): \_\_\_\_\_ Length (inches): \_\_\_\_\_  
 - Height (inches): \_\_\_\_\_ Weight (lbs): \_\_\_\_\_  
 Min:  
 - Width (inches): \_\_\_\_\_ Length (inches): \_\_\_\_\_  
 - Height (inches): \_\_\_\_\_ Weight (lbs): \_\_\_\_\_  
 Description: \_\_\_\_\_  
 Max. Qty.: \_\_\_\_\_ Total Live Load\*: \_\_\_\_\_  
 Temperature  
 -Environment: \_\_\_\_\_  
 -Product: \_\_\_\_\_  
 Wet  Dry  Other \_\_\_\_\_

### Conveyor Construction:

- Welded
  - Painted  Epoxy Painted
  - Powder Coated
- Stainless Steel
  - Mill Finish
  - Blasted
    - Sand Bead  Glass Bead
  - Polished
  - Bolt-Together Galvanized

### Conveyor Orientation:

- Horizontal
- Incline: \_\_\_\_\_ TOB - \_\_\_\_\_ TOB
- Decline: \_\_\_\_\_ TOB - \_\_\_\_\_ TOB
- Curve: \_\_\_\_\_ IR

### Conveyor Bed Type:

- Slider Bed
- Open Style Slider Bed
- Roller Bed

### Conveyor Length:

\_\_\_\_\_ Feet \_\_\_\_\_ Inches

### Support Type:

- Legs  Ceiling Supports
- None  Top of Belt: \_\_\_\_\_

### Belt Specs:

Belt Width: \_\_\_\_\_ Inches  
 Belt Style: \_\_\_\_\_ (i.e. 1/2 x 1, 1x1, etc.)

### Belt Material:

- Galvanized  High Carbon
- Stainless Steel

### Speed:

- Fixed  Variable Low Speed: \_\_\_\_\_  
 High Speed: \_\_\_\_\_
- AC Speed Controller  DC Speed Controller

### Drive Type:

- Under Hung  Shaft Mount  Side Mount
- Overtop Drive

### Plant Voltage:

- 110V Single Phase  460V Three Phase
- 220V Single Phase  208V Three Phase
- 220V Three Phase  575V Three Phase

Other: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_