

AID Equipment (Salt Lake City, UT branch) Phone: 801.566.2112 Sales@aideq.com www.aideq.com

## **ZERO PRESSURE CDLR QUOTATION WORKSHEET**

☐ Mechanical Variable Speed Adjustment

□ No

**Approval Drawing Required:** ☐ **Yes** 

Company	Date					
Contact Quote						
		:State				
Omni Sales Contact:						
Quantity:						
Bundant Curan		Overterner De				
Product Specs:		Customer Re	questea nors	epower:		
Max: Width (inches): Length (inches):		Plant Voltage				
Height (inches): Weight (lbs):		110V Sir		☐ 460V Three	Phase	
Min:	_		•	208V Three		
		220V Thi	-	□ 575V Three		
Width (inches): Length (inches):			ice i nase	<b>2</b> 0/0 <b>V</b> 111100	1 11000	
Height (inches):Weight (lbs):		Application Information:				
Description:		= =	Product Enters By:			
Max. Qty.: Total Live Load:		☐ Conveyed On ☐ Fork Truck				
		☐ Robot		☐ Other		
Temperature		Product Exits By:				
Environment:		☐ Conveyed off ☐ Fork Truck				
Product:		☐ Robot ☐ Other				
Product:		Interfacing with:				
☐ Pallet (Right Way) ☐ Pallet (Wrong Way) ☐ Box☐ Slip Sheet ☐ Rack (Picture Frame) ☐ Barrel	Ctooker			☐ Destacker ☐ Wrapper		
☐ Rack (Solid Bottom) ☐ Other		☐ Elevator ☐ Scale Other				
Material:	Workstations:					
☐ Wood ☐ Plastic ☐ Steel ☐ Cardboard		☐ Qty ☐ Product Removed from Workstation			Workstation	
Other		Chain Transfers:				
☐ Qty Flow: ☐ On ☐ Off						
Conveyor Construction:						
☐ Welded		Accessories:				
☐ Painted ☐ Epoxy Painted ☐ Stainless Ste	el	☐ Endstops ☐ Sideguides ☐ Funnel Guides				
☐ Powder Coated Color RAL:						
		Other:				
Conveyor Specifications:		Other.				
Length Effective Width Roller Diameter						
Roller Centers						
Zone Quantity						
Rollers Set: Low/Low High/Low		-				
TOR (Top of Roller Height)		Standard Specifications				
Drive Mount: High Low Below and Within	ſ	Standard	1.9 Roller	2 1/2 & 2 9/16 Roller	3 1/2 Roller	
Controls:	ı	Frame	6 x 8.2#[	6 x 8.2#[	6 x 8.2#[	
☐ Sensor Roller ☐ Sick Optics ☐ Photoeye & Va☐ None ☐ Special		Capacity Per Zone	1500 lbs.	3500 lbs.	6000 lbs	
Trone Georgia	- ⊦	Maximum HP	2	2	2	
Speed: F.P.M.:	Ratio)	Effective Widths	13" - 39"	16" - 72"	16" -99"	
☐ AC Speed Controller ☐ DC Speed Controller	´	Overall Width	BF + 12 3/8"	BF + 12 3/8"	BF + 13 5/8"	

Zone Lengths

Minimum TOR

36" - 72"

10"

36" - 72"

10"

36" - 72"

12"