



## ZERO PRESSURE LINESHAFT DRIVEN LIVE ROLLER CONVEYOR QUOTATION

Company \_\_\_\_\_ Date \_\_\_\_\_  
 Contact \_\_\_\_\_ Quote Due \_\_\_\_\_ Desired Delivery \_\_\_\_\_  
 Phone No. \_\_\_\_\_ Contact Email \_\_\_\_\_ State \_\_\_\_\_  
 Omni Sales Contact \_\_\_\_\_ Quote #: \_\_\_\_\_  
 Quantity \_\_\_\_\_

### Product Specs:

Max:  
 - Width (inches): \_\_\_\_\_ Length (inches): \_\_\_\_\_  
 - Height (inches): \_\_\_\_\_ Weight (lbs): \_\_\_\_\_  
 Min:  
 - Width (inches): \_\_\_\_\_ Length (inches): \_\_\_\_\_  
 - Height (inches): \_\_\_\_\_ Weight (lbs): \_\_\_\_\_  
 Description: \_\_\_\_\_  
 Max. Qty.: \_\_\_\_\_ Total Live Load: \_\_\_\_\_  
 Temperature  
 -Environment: \_\_\_\_\_  
 -Product: \_\_\_\_\_

### Drive Type:

- Underhung (21 1/4 in. min. top of roller)  
 Side Mount (10 3/4 in. min. top of roller)  
 Timing Belt  Chain

### Plant Voltage:

- 110V Single Phase  440V Three Phase  
 220V Single Phase  208V Three Phase  
 220V Three Phase  575V Three Phase

Other: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### Conveyor Construction:

- Bolt-Together  
 Galvanized (STD)  Finish Coat  
 Welded/Finish Coat (Req'd on BF's greater than 39 in.)

### Finish Coat:

- Paint Color: \_\_\_\_\_  
 Powder Coat Color (RAL #): \_\_\_\_\_

### Roller Specs.:

- 1 3/8 in. dia. Roller c/c: \_\_\_\_\_  
 1-1/2 in. (Photo eye only)  
 1.9 in. dia. Roller c/c: \_\_\_\_\_  
 3 in., 4 in., 6 in. or 8 in. (Trigger Roller or Photo eye)

### Between Frames Width:

- \_\_\_\_\_ 13 in. thru 28 in. for 1 3/8 in. dia. Roller  
 \_\_\_\_\_ 13 in. thru 39 in. for 1.9 in. dia. Roller

### Support Type:

- Legs  Ceiling Supports  None  
 TOR: \_\_\_\_\_

Flow: Standard \_\_\_\_\_ Opposite \_\_\_\_\_

### Speed:

- FPM: \_\_\_\_\_  Fixed  Variable (10:1 ratio)  
 60 FPM (Standard) 25-120 FPM Available (Standard)  
 AC Controller  DC Controller  Less Controller

**NOTE:** If speed is variable, specify maximum.  
 Minimum is always 25 FPM.

Approval Drawing Required:  Yes  No

