

Extra Wide Bumper Guard for R&B Wire® Poly Bumper Trucks



Eliminate Damage - Reduce Repair Costs - Increase Staff Efficiency

- Eliminate damage to facility caused by laundry/utility trucks
- Reduce operating costs for repairs & cosmetic touch-ups
- Housekeeping staff can quickly maneuver carts without damaging walls, doorframes and elevators

Enclosed:

- □ 1 Extra Wide Bumper Guard
- 24-inch Velcro° strips
- 6-inch Velcro® strips
- □ 4 2-inch Velcro strips

Additional supplies needed:

☐ Rubbing alcohol or a non-oil-based cleaning solution **Important:** DO NOT USE BLEACH PRODUCTS

Step 1: Prepare Cart for Velcro Installation

Clean Cart: Dirt and bleach products will prevent Velcro° adhesive from adhering well. Clean top-edge of Poly Truck with rubbing alcohol or a non-oil-based cleaning solution.

Step 2: Bumper Guard Installation





- Fig 2.1 Installation process begins on narrow-end of cart. Attach the 6-inch Velcro adhesive strip along top-edge of cart as shown above.
- Fig 2.2 Center "DuraBumper" logo on narrow-end of cart. Attach bumper guard onto Velcro and press firmly into place. The remaining portion of bumper should rest inside cart.





Fig. 2.3

- Fig 2.3 Slip bumper guard over top-edge of cart as shown in photo.
- Fig 2.4 Beginning on long-side of cart (Side A):
 - a. Pull bumper BELOW top-edge of cart, exposing two corners.
 - b. Attach Velcro strips along cart's top-edge above the manufacturers bumper:
 - □ 24-inch Velcro on long-side of cart
 - □ 6-inch Velcro on remaining narrow-end
 - □ 2-inch Velcro on the two exposed corners

Step 2: Bumper Guard Installation (continued)





Fig. 2.5

Fig. 2.6

- Fig 2.5 Pull bumper guard up and over each corner and align top-edge of bumper with Velcro. Once bumper is attached to corners, pull bumper guard up and over cart's long-side and align top-edge of bumper with Velcro.
- Fig 2.6 Press bumper securely into place.

Preform Steps 2.4a through 2.6 for Side B

Bumper Guard Installation Complete



Extend the Life of Bumper Guard

As corners of bumper begin to wear over time, gradually rotate bumper around cart.