

50Ω Divide-BY-4, 4-18 GHz

Case PN: 6UDD2W6S1A2

Features:

- Divide by M: (M = 4)
- Ultra Low SSB Phase Noise -150 dBc/Hz
- Input frequency range: 4-18 GHz
- Output Power: -5 dBm
- Single DC Supply: +3.3V
- Low Power Consumption: 30 mA
- Rugged, shielded case (SMA Connector)

Applications:

- Cellular, Satellite Communication Systems
- PCS, W-CDMA, ISM, LTE
- SDR & Ham Radio



Electrical Specifications (Test Conditions: T_A = +25°C, 50 Ohm System, V_{cc}=+3.3V)

No.	Parameter	Conditions	Electrical Specification			
			MIN	TYP.	MAX	UNITS
1	Input Freq.		4		18	GHz
2	Input Power Range		-10		+10	dBm
3	Output Power		-10	-5		dBm
4	Reverse Leakage	RF Output Terminated, Pin=0 dBm, Fin=8 GHz		-60		dBm
5	SSB Phase Noise (100 kHz offset)	Pin=0 dBm, Fin=12 GHz		-150		dBc/Hz
6	Power Supply		3.0	3.3	3.6	V
7	Supply Current (I _{cc})	V _{cc} = 3.3 V		30	60	mA

Absolute Maximum Ratings

Item	Parameter	Rating	UNITS
1	RF Input Power (V _{cc} = +5V)	10	dBm
2	V _{cc}	+3.9	V
3	Storage Temperature	-65 to +150	°C
4	Operating Temperature	-40 to +105	°C

Outline Drawing (Inch)

