

## Technical Data Sheet (valid from batch #80000)

## **KUNOS Finishing Oil No. 240**

## new quality

N means LIVOS neutral for the allergy-prone and chemically sensitive

### Without orange oil

**Application range** In the interior, for maintenance, after-treatment of with LIVOS products oiled countertops, solid wooden

furniture, floors and stairs, as well as brushed or profiled wood.

**Technical qualities** After polishing semi-glossy, water-repellent surface. Complies with the German Industrial Norm DIN 53

160 for color fastness when exposed to perspiration and saliva. Free of organic-chemical compounds

according to DIN EN 71 part 9.

Full declaration Isoaliphates, linseed oil - stand oil - natural resin ester, micronized wax, dehydrated castor oil, dehydrated

amino sugar and drying agents free of lead. (Mn, Zr)

Color 002 clear

**Application method** By brush or wadded cloth, on large areas with a single disc rotary machine and felt pad.

1-2 applications at temperatures above 18 °C (64 °F).

**Coverage** Determine the exact amount needed by doing a test application.

1 liter (1.06 quart.) is sufficient for appr. 100 m<sup>2</sup> (1076ft<sup>2</sup>), i.e. 10 ml/m<sup>2</sup>.

**Cleaning** Clean equipment immediately after use with SVALOS Thinner No. 222 or LEVO Brush Cleaner No. 997.

**Drying time** At 23°C (73°F) and a relative humidity of 50%: 16 - 24 hours. Final durability is reached after 4 weeks.

At higher temperatures, please consider shorter drying times and polish more quickly. At lower temperatures and higher humidity, please consider longer drying times.

**Specific gravity** Approximately 0.85 g/ml.

Safety advice Ensure good ventilation during and after application. Always be sure to store cleaning cloths, polishing

pads, sponges, etc. that are still wet or even slightly moist with KUNOS Finishing Oil No. 240 in an airtight metal container or in water until their disposal, as there is a danger of combustion caused by the plant oil

content. The liquid or applied product is not self-ignitable.

P102 Keep out of reach of children.

**P301+P310** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor.

**Disposal** According to locally regulated laws.

**Container Size** 0.25 l; 0.75 l; 2.5 l; 10 l.

**Storage** Cool and dry. Shelf life: unopened at least 4 years. Opened products react with oxygen, over time skin

formation and rancid smell can occur. Residues should be transferred into smaller containers.

LIVOS Plant Chemistry D - 29559 Wrestedt OT Emern · Tel. +49 58 25 / 88 - 0 · Fax 88 60 · www.livos.de · info@livos.de

#### How to use

# **KUNOS Finishing Oil No. 240**

#### **Counter tops, Stairs**

#### **Preparation:**

Oiled wooden surfaces must be dry, clean and free of dust.

Sand any existing watermarks with 320 grain and treat the surface 1 – 2x with the initial product until the gloss level of the remaining area is reached.

#### **Processing:**

Remove possible skin formed on surface in case of already opened containers and then stir thoroughly.

Test application!

Apply Finishing Oil generously and wipe off excess oil after 5 minutes with a lint-free cotton cloth. The next day (after 16 hours), apply the Finishing Oil generously again and polish after 5 minutes.

#### **Floors**

On oiled surfaces, which have uniform gloss, spread Finishing Oil drop by drop (1 TS [Tablespoon] =  $5-8 \text{ g/m}^2$ ). Polish immediately with a grain free pad (beige or felt) wetted with Finishing Oil, or with a polishing- pad or -machine. Stripes should be avoided; check in the backlight. The whole procedure should be repeated if necessary.

#### Cleaning and Maintenance

Clean with TRENA pH-Neutral Cleaner No. 556 diluted in water and with a moist but not wet cloth. Every 4<sup>th</sup> to 5<sup>th</sup> cleaning should be done with GLANOS Natural Liquid Wax Cleaner No. 559 instead of TRENA.

After-treatment depending on the usage, usually 1-2 times a year with KUNOS Maintenance No. 1862, if the surface looks matt.

#### **Important tips**

With brushed wooden surface, or when the surface was profiled with special tools, apply Finishing Oil generously 1x and spread on the surface standing oil after 5 minutes with a hard brush or similar. Then apply 2 sparing coats with intermediate drying.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the LIVOS customer service.

March 2019