

## Product Description

Infinity Bond E2190 is a formulated hot melt primarily designed for uncoated stock case and carton sealing and erecting. Infinity Bond E2190 has a very fast set speed, medium open time, aggressive tack, excellent adhesion, and good heat stability. Good high and low temperature bond performance. Product is suitable for all equipment generally associated with packaging applications.

## Physical Properties

Viscosity @ 350F	1000 cps
Softening Point	228°F
Color	Amber
Application Temperature	330-360°F
Open Time	<15 Seconds

## Features & Benefits

- Very fast set speed
- Medium open time
- Aggressive tack
- Good high and low temperature performance

## Handling & Storage

For best results use this product within 365 days.

## Safety

When handling and working with hot melt adhesives wear protective clothing and eye protection at all times. To minimize the risk of flammable vapors, do not exceed 400°F melt temperature.

## Clean Up

For best results, allow product to cool and manually remove excess adhesive with scraper. Consult your hot melt equipment manufacturer for proper clean-up procedures or contact your Infinity Bond representative for additional help.

## FDA Status

Approved under the Federal Regulation 21 CFR 175.105 which related to incidental contact of adhesive with food.

## Rotate Stock

For best results, use oldest lots first.

## Toxicity

Under normal conditions of use this product is considered nontoxic. Consult the SDS for additional information.

## Note to Customers

Technical data contained within this document is intended for reference only. For assistance and recommendations on specifications for this product, contact Infinity Bond Adhesives.