

superDOT **E126**

Stitch and Dot Optimized EVA Packaging Hot Melt

Use up to 50% less adhesive

superDOT E126 is a premium hot melt adhesive formulated for applications using hot melt stitching and dotting to reduce adhesive consumption up to 50%. It is a freezer grade adhesive and is also used for bonding coated stocks and difficult substrates. It offers a fast hot tack and strong bond to a wide range of packaging substrates.

TYPICAL PROPERTIES

Application Temperature Range.....	325-365 °F
Viscosity @ 350°F.....	1,250 cps
Softening Point.....	160 °F
Open Time.....	Short
Product Form.....	Chips

FEATURES

- Freezer Grade
- Bonds Coated and Difficult Stock
- Good Heat and Cold Resistance
- Strong, Fast Tack
- Freezer Grade

COMMON APPLICATIONS

- High Speed Packaging
- Semi-Automated Packaging
- Food Packaging
- Freezer Applications

BONDS TO

- Cardboard
- Corrugated
- Paper
- Coated Stocks
- Difficult Substrates

AVAILABLE FORMS

- Bulk Hot Melt - Chips

IMPORTANT NOTICE TO CUSTOMER

The information herein is general information designed to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We require customers to inspect and test our products before use to and to satisfy themselves as to contents and suitability for their specific applications. We warrant that our products will meet our written specifications. Nothing herein shall constitute any other warranty express or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.