



**tec 4500B & tec 4500S**

**Pneumatic reservoir gun for bulk and shaped hot melts**

**Bead and spray models**



Bead



Spray

**For bulk & shaped glue**



Bulk - pillows



Bulk - granules



Bulk - slats



Shaped

**Plus**

**Decreased operator fatigue**

**Intelligent design**

**Quick start up**

**tec 4500B**



**tec 4500S**



NEW · NEW · NEW · NEW

**For bulk AND shaped hot melts**

**Versatile**

The tec 4500 is a highly versatile tool that can be supplied as a bead or spray applicator. Uniquely, it can also be used with bulk and shaped adhesives.

**For bulk & shaped glue**

Features a built-in melt chamber and pre-set temperature that allow the tec 4500 to take EVA, polyolefines, or pressure sensitive adhesives (PSA) in granular form, pillows, or 43mm (1¾") slugs.

**Decreased operator fatigue**

Offering reliability and user-comfort, the tec 4500 ensures effortless work for the operator. Ergonomically designed and lightweight, the gun quickly and easily applies even large amounts of adhesive in bead, dot, or spray form.

**Intelligent design**

The innovative melt chamber allows the tec 4500 to take both bulk and shaped adhesives. It also features a one-handed twist action lock for quick & easy loading of the glue tank. The soft-closing mechanism ensures efficient energy consumption and the highest possible melt rate.

**Additional features**

The tec 4500 also boasts a quick start up, cutting down on warm-up time and making it ready for use, fast. It is lightweight for easy, one-handed operation, and comes with a detachable stand for increased freedom of movement when in use.



**tec4500B & tec4500S**

Reliable, easy to use glue gun with a built-in melt chamber that allows the use of adhesives in granular form, pillows, or 43mm (1¾") slugs. Available in bead (4500B) or spray (4500S) models.

<b>Melt rate</b>	Granular: 1kg (2lbs) - Slugs: 2.5 kg (5½lbs)/hr
<b>Glue size</b>	Granules & 43mm (1¾") glue cartridge
<b>Voltage</b>	220 - 240V
<b>Wattage</b>	600W
<b>Heater</b>	Cartridge
<b>Temp Control</b>	Preset thermostat
<b>Hotmelt gun °C (°F)</b>	180 - 190°C
<b>Lowmelt gun °C (°F)</b>	n/a
<b>Power cable</b>	3m (10 ft)
<b>Weight</b>	4500B: 1.25kg (2.7lbs) 4500S: 1.45kg (3.2lbs)
<b>Packaging</b>	Plain box (1 per ctn)

