

All-electric
bead gun



tec 3150

High output 43mm (1¾") glue gun for industrial use. All-electric & extremely robust. Power-on light with removable integral stand with built in nozzle spanner.

Melt rate	3kg (6½ lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	300W
Heater	Cartridge
Temp Control	Interchangeable thermostat
Hotmelt gun °C (°F)	195°C (380°F)
Lowmelt gun °C (°F)	130°C (265°F)
Power cable	3m (10 ft)
Weight	1.15kg (2½lbs)
Packaging	Plain box (5 per ctn)

Pneumatic
bead gun



tec 6100

Extremely robust 43mm (1¾") pneumatic glue gun for Industrial use. Reduces operator fatigue, power-on light, 8 bar (120psi) 14 l/min (0.5 cfm) air supply required.

Melt rate	4.1kg (9lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	500W
Heater	Cartridge
Temp Control	Interchangeable thermostat
Hotmelt gun °C (°F)	195°C (380°F), High temp polyamide version 215°C (420°F) also available
Lowmelt gun °C (°F)	130°C (265°F)
Power cable	3m (10 ft)
Weight	1.4kg (3lbs)
Packaging	Plain box (5 per ctn)

Pneumatic
bead gun



Speedloader
to reduce
down time!



tec 7100

Extremely robust, very high output 43mm (1¾") pneumatic glue gun for industrial use. Reduces operator fatigue, speed loader to save time and power-on light. 8 bar (120psi) 14 l/min (0.5 cfm) air supply required.

Melt rate	5.0 kg (11lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	1000W
Heater	Cartridge
Temp Control	Interchangeable thermostat (Contact distributor)
Hotmelt gun °C (°F)	195°C (380°F)
Lowmelt gun °C (°F)	130°C (265°F)
Power cable	3m (10 ft)
Weight	2.3kg (5lbs)
Packaging	Plain box (5 per ctn)

Don't forget!



You'll need to use an air compressor with the tec 6100 & tec 7100. You can find the **tec-AIR 50TDC** on page 22.