

All-electric bead gun



tec 3150

High output 43mm (1¾") glue gun for industrial use. All-electric & extremely robust. Power-on light with removable integral stand with built in nozzle spanner.

Melt rate	3kg (6½ lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	300W
Heater	Cartridge
Temp Control	Interchangeable thermostat
Hotmelt gun °C (°F)	195°C (380°F)
Lowmelt gun °C (°F)	130°C (265°F)
Power cable	3m (10 ft)
Weight	1.15kg (2½lbs)
Packaging	Plain box (5 per ctn)

Pneumatic bead gun



tec 6100

Extremely robust 43mm (1¾") pneumatic glue gun for Industrial use. Reduces operator fatigue, power-on light, 8 bar (120psi) 14 l/min (0.5 cfm) air supply required.

Melt rate	4.1kg (9lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	500W
Heater	Cartridge
Temp Control	Interchangeable thermostat
Hotmelt gun °C (°F)	195°C (380°F), High temp polyamide version 215°C (420°F) also available
Lowmelt gun °C (°F)	130°C (265°F)
Power cable	3m (10 ft)
Weight	1.4kg (3lbs)
Packaging	Plain box (5 per ctn)

Don't forget!



You'll need to use an air compressor with the tec 6100 & tec 7100. You can find the **tec-AIR 50TDC** on page 22.

Pneumatic bead gun



Speedloader to reduce down time!



tec 7100

Extremely robust, very high output 43mm (1¾") pneumatic glue gun for industrial use. Reduces operator fatigue, speed loader to save time and power-on light. 8 bar (120psi) 14 l/min (0.5 cfm) air supply required.

Melt rate	5.0 kg (11lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	1000W
Heater	Cartridge
Temp Control	Interchangeable thermostat (Contact distributor)
Hotmelt gun °C (°F)	195°C (380°F)
Lowmelt gun °C (°F)	130°C (265°F)
Power cable	3m (10 ft)
Weight	2.3kg (5lbs)
Packaging	Plain box (5 per ctn)