# **Safety Data Sheet**



Revision Number: 004.0 Issue date: 11/29/2022

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: TECHNOMELT PUR 508 known as IDH number: 542663

PURMELT R-508

**Product type/use:** 1-component-polyurethane adhesive **Restriction of Use:** 1-tomponent polyurethane adhesive This product is for industrial use only.

Company address:

Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Region: United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.

STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR

FLAMMABLE VAPORS MAY CAUSE IGNITION.

VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND

RESPIRATORY TRACT IRRITATION.

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING

DIFFICULTIES IF INHALED.

CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED

EXPOSURE.

| HAZARD CLASS                                       | HAZARD CATEGORY |
|--|-----------------|
| SKIN IRRITATION                                    | 2               |
| EYE IRRITATION                                     | 2A              |
| RESPIRATORY SENSITIZATION                          | 1               |
| SKIN SENSITIZATION                                 | 1               |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 1               |

#### PICTOGRAM(S)



#### **Precautionary Statements**

Prevention:

Do not breathe dust or fumes. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection. In case of inadequate

ventilation wear respiratory protection.

Response:

IF ON SKIN: Wash with plenty of water. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician. Take

off contaminated clothing.

Storage: Not prescribed

IDH number: 542663 Product name: TECHNOMELT PUR 508 known as PURMELT R-508

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)   | CAS Number  | Percentage* |
|--|-------------|-------------|
| Hexanedioic acid, polymer with butyl 2-methyl-2-propenoate, 1,6-hexanediol, a-hydro-w-hydroxypoly[oxy(methyl-1,2-ethanediyl)],2-hydr | 345907-06-4 | 90 - 100    |
| Methylenebis(phenylisocyanate)   | 101-68-8    | 1 - 5       |
| Methylene bisphenyl isocyanate   | 26447-40-5  | 0.1 - 1     |

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If not

breathing, give artificial respiration.

Skin contact: Cool melted product on skin with plenty of water. Do not remove solidified

product. Immediately wash skin thoroughly with soap and water. Get

immediate medical attention.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Continue to flush eyes while awaiting medical attention

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel. Seek

medical advice.

Symptoms: See Section 11.

Notes to physician: Persons with asthmatic-type conditions, chronic bronchitis, other chronic

respiratory diseases or recurrent skin eczema or sensitization should be

excluded from working with isocyanates.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

**Special firefighting procedures:** Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and

nitrogen oxides (NOx) can be released. Irritating and toxic gases or fumes

may be released during a fire. Hydrogen cyanide.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Keep unnecessary personnel away. Wear protective clothing, gloves and

safety glasses. If product is spilled in the solid state, pick up and place in an appropriate waste disposal container. If product is spilled in the molten state, allow product to solidify before scraping up and disposing of in an appropriate

waste disposal container.

IDH number: 542663 Product name: TECHNOMELT PUR 508 known as PURMELT R-508

### 7. HANDLING AND STORAGE

Handling: Do not place wet or damp solid into melt tank. Avoid skin and eye contact.

Avoid breathing vapors or mists of this product. Wash thoroughly after

handling.

Storage: Store in tightly closed containers to prevent moisture contamination. Reacts

slowly with water to liberate carbon dioxide gas. Do not store above 100 °F

(37.7 °C).

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)   | ACGIH TLV     | OSHA PEL                        | AIHA WEEL | OTHER |
|--|---------------|---------------------------------|-----------|-------|
| Hexanedioic acid, polymer with butyl 2-<br>methyl-2-propenoate, 1,6-hexanediol, a-<br>hydro-w-hydroxypoly[oxy(methyl-1,2-<br>ethanediyl)],2-hydr | None          | None                            | None      | None  |
| Methylenebis(phenylisocyanate)   | 0.005 ppm TWA | 0.02 ppm (0.2<br>mg/m3) Ceiling | None      | None  |
| Methylene bisphenyl isocyanate   | None          | None                            | None      | None  |

Engineering controls: Work should be done in an adequately ventilated area (i.e., ventilation

sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below

occupational exposure limits.

Respiratory protection: No personal respiratory protective equipment normally required. Do not inhale

vapors and fumes. Concentrations greater than the TLV can occur when MDI is sprayed, heated or used in a poorly ventilated area. A positive pressure,

supplied-air respirator or a self-contained breathing apparatus is

recommended when: airborne concentrations of isocyanate are known to exceed 0.005 ppm; operations are performed in a confined space or area with limited ventilation; material is heated or sprayed. Observe OSHA regulations

for respirator use (29 CFR 1910.134).

**Eye/face protection:** Safety glasses with sideshields or chemical safety goggles should be worn if

there is a risk of splashing. Full face protection should be used if the potential

for splashing or spraying of product exists.

**Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:SolidColor:WhiteOdor:CharacteristicOdor threshold:Not available.

pH: Not applicable Vapor pressure: Not available. Boiling point/range: Not available.

Melting point/ range: 65 °C (149°F) (Softening Point)

Specific gravity: 1.2

Vapor density: Not determined

Flash point: > 200 °C (> 392°F) Cleveland open cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability:

Flammability:

Flammability:

Not applicable

Not applicable

Not applicable

Solubility in water: Not soluble. Reacts with water to liberate carbon dioxide gas.

Partition coefficient (n-octanol/water): Not applicable

VOC content: 0 g

Viscosity: 7,500 - 11,500 cp Decomposition temperature: Not available.

IDH number: 542663 Product name: TECHNOMELT PUR 508 known as PURMELT R-508

## 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition

Incompatible materials:

Thermal decomposition can lead to release of irritating gases and vapors. Hydrogen cyanide. Oxides of carbon. Oxides of nitrogen.

products:

Reacts with alcohols and amines. Reacts slowly with water to liberate carbon dioxide gas.

Reactivity: Not available.

Conditions to avoid: Container can be pressurised by carbon dioxide due to reaction with humid air and/or water.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation: Methylene bisphenyl isocyanate (MDI) vapors or mist at concentrations above the TLV can

irritate the mucous membranes in the respiratory tract (nose, throat, lungs) causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing obstruction). This product may cause sensitization by inhalation and skin contact. Repeated exposure may lead to respiratory sensitization reactions, producing an asthma-like

condition.

Skin contact: Repeated or prolonged skin contact may result in allergic sensitization. May cause skin

irritation. Molten adhesive may cause severe burns. Liquid or vapor can cause moderate to severe irritation.

**Eye contact:** Liquid or vapor can cause moderate to severe irritation. **Ingestion:** Harmful if swallowed. Not expected under normal conditions of use.

| Hazardous Component(s)   | LD50s and LC50s | Immediate and Delayed Health Effects     |
|--|-----------------|--|
| Hexanedioic acid, polymer with butyl 2-<br>methyl-2-propenoate, 1,6-hexanediol, a-<br>hydro-w-hydroxypoly[oxy(methyl-1,2-<br>ethanediyl)],2-hydr | None            | No Records                               |
| Methylenebis(phenylisocyanate)   | None            | Irritant, Respiratory, Allergen          |
| Methylene bisphenyl isocyanate   | None            | Allergen, Irritant, Mutagen, Respiratory |

| Hazardous Component(s)   | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|----------------|-----------------|--|
| Hexanedioic acid, polymer with butyl 2-<br>methyl-2-propenoate, 1,6-hexanediol, a-<br>hydro-w-hydroxypoly[oxy(methyl-1,2-<br>ethanediyl)],2-hydr | No             | No              | No                                       |
| Methylenebis(phenylisocyanate)   | No             | No              | No                                       |
| Methylene bisphenyl isocyanate   | No             | No              | No                                       |

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

#### Information provided is for unused product only.

Recommended method of disposal: This product is not a RCRA hazardous waste wh

This product is not a RCRA hazardous waste when discarded. Processing, use, or contamination of this product may change the hazard classification and waste management options. Dispose of according to Federal, State and local governmental regulations.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

None

None

None

None

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Methylenebis(phenylisocyanate) (CAS# 101-68-8).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

#### **Canada Regulatory Information**

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 15

Prepared by: Regulatory Affairs

**Issue date:** 11/29/2022

IDH number: 542663 Product name: TECHNOMELT PUR 508 known as PURMELT R-508

Page 5 of 6

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.