3M

Performance Plus Duct Tape

8979

Technical Data	June, 2010

Product Description

3MTM Performance Plus Duct Tape 8979 has a unique product construction for indoor and outdoor applications. This tape is removable with little or no adhesive residue from most opaque surfaces up to six months after application. 3MTM Performance Plus Duct Tape 8979 is also resistant to delamination and deterioration when exposed to UV outdoors for up to one year.

Product Construction	Backing	Adhesive	Colors	Standard Roll Lengths
	Polyethylene film	Rubber	Black, Olive,	54.8 m (60 yds.)
	over cloth scrim		Slate Blue	22.9 m (25 yds.)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	48 oz./in. width (53 N/100 mm)	D-3330
Tensile Strength:	36 lbs./in. width (630 N/100 mm)	D-3759
Elongation at Break:	19%	D-3759
Tape Thickness:	12.1 mils (0.31 mm)	D-3652
Temperature Use Range:	Up to 200°F (93°C)	

Features

- Tested in accordance with UL 723 / ASTM E84.
- Backing is curl resistant, moisture resistant and conformable making the tape easy to handle and apply.
- High tensile strength for the most demanding applications.
- · Hand-tearable.
- Rubber adhesive bonds well to many surfaces with excellent initial stick.
- Unwinds easily from the roll to minimize user fatigue.
- Distinctive slate blue color available.