This page is also available in a language that may suit you better:

United Kingdom

English

80H

STAY ON THIS PAGE



Q **≡** 


Industry



tesa® ACX<sup>plus</sup> 7283 Multi Purpose (MP)

 $800~\mu m$  double-sided acrylic foam tape





✓ PFAS/PFOS free product

# **Product description**

tesa® ACX<sup>plus</sup> 7283 MP is a black double-sided acrylic foam tape.

# **Application Fields**

The tesa® ACX<sup>plus</sup> MP product family is suitable for a wide range of multi-purpose bonding applications.

To ensure the highest performance possible, our aim is to fully understand the application (including the substrates involved) in order to provide the right product recommendation. tesa® ACX<sup>plus</sup> 7283 MP series is especially suitable for bonding applications such as emblem, decorative part or signage mounting.

Additionally, tesa® 7283 perfectly fits for the application on surfaces with low surface energy, e.g. plastics/PE.

### **Product Construction**

Type of adhesive	foamed acrylic blend
Total thickness	800 μm
Backing material	foamed acrylic
Color	black

### Adhesion to Values

Adhesion to Aluminium (after 3 days)	28 N/cm
Adhesion to Steel (after 3 days)	27 N/cm
Adhesion to PE (after 3 days)	4.5 N/cm

#### **Additional Info**

Please note that we recommend using tesa® Adhesion Promoter as a surface pre-treatment. It leads to a significant improvement in adhesion levels, avoids moisture infiltration, and promotes long-term resistance against harsh environmental factors. Which tesa® Adhesion Promoter should be used depends on the substrates and the application. We will be glad to advise you in order to find the right solution.

Liner versions:

• PV42: White paper liner - branded

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical staff will be glad to support you.

## **Downloads**